



EconoMax Boom

BOM104 For Calm Water & Low Current, 50' x 16", 10" Draft Dimensions

Economical non-absorbent floating booms provide 1,800 lb. of actual breaking strength to contain waterborne oil spills and debris on calm water.

- Rectangular, closed-cell polyethylene foam flotation blocks corral liquids and debris up to 6" above the water line
- Skirting barrier hangs 10" below the water line to keep pollutants from creeping under
- Galvanized steel chain runs the length of the boom to add weight and rigidity
- Heavy-duty, 22-ounce vinyl-coated polyester is UV resistant for regular outdoor use
- Welded, reinforced seams ensure long life
- Marine-grade aluminum universal slide connectors and attached toggle pins let you link multiple booms
- Quality construction provides 1,800 lb. actual breaking strength
- Compact size allows easy deployment
- High-visibility yellow for instant recognition in emergencies
- Conforms to OPA-90 specifications; ideal for economical use in inner harbors, marinas and waterways
- Cleans easily using detergents, steam or power washing
- Add PIG Oil-Only Booms to absorb petroleum-based pollutants
- Need a custom boom? Call 1-800-HOT-HOGS (468-4647)

Specifications

Style	Non-Absorbent Boom
Dimensions	50' L x 16" H
Application	Spill Response
Brand	Elastec American Marine
Current Type	Calm Water & Low Current
Draft Dimensions	10"
Color	Yellow
Freeboard Dimensions	6"
Intended Use	On Water
Distributor Part Number	5759444;04088x00382

Sold as	1 each
Weight	70 lbs.
# per Pallet	4
Composition	Boom - PVC Chain - Galvanized Steel
UNSPSC	24101907
Pigalog® Page Number	<u>Page 185</u>

Metric Equivalent

Dimensions	15m L x 40.6cm H
Weight	31.8 kg

Technical Information

Technical Documents

33 CFR 154.1040

40 CFR 112.7

40 CFR 122.26



One Pork Avenue • Tipton, PA 16684-0304

1-855-493-4647 • Fax: 1-800-621-7447 • newpig.com • hothogs@newpig.com