

Simplex™ Boom

BOM107 For Strong Current, 100' x 18", 12" Draft Dimensions

Marine-grade aluminum connectors and a galvanized steel chain make this 5,000 lb. breaking strength non-absorbent floating boom great for containing oil spills and debris in strong currents.

- Round, closed-cell polyethylene foam flotation cylinders corral liquids and debris up to 6" above water line
- Skirting barrier hangs 12" below the water line to keep pollutants from creeping under; galvanized steel chain runs the length of the boom to add weight and rigidity
- Heavy-duty, 22-ounce vinyl-coated polyester is UV resistant for regular outdoor use; welded, reinforced seams help ensure long life
- Marine-grade aluminum universal slide connectors and attached toggle pins permit linking of multiple units
- Quality construction provides 5,000-lb. actual breaking strength
- Polypropylene handle/anchor point eases handling and securing for easy deployment
- High-visibility yellow for instant recognition in emergencies
- Conforms to OPA-90 specifications
- Cleans easily using detergents, steam or power washing
- Light-weight and easy to move; ideal in marinas, inland waterways or along shorelines
- Add PIG Oil-Only Booms to absorb petroleum-based pollutants
- Need a custom boom? Call 1-800-HOT-HOGS (468-4647)



Specifications

Style	Non-Absorbent Boom
Dimensions	100' L x 18" H
Application	Spill Response
Brand	Elastec American Marine
Current Type	Strong Current
Draft Dimensions	12"
Color	Yellow
Freeboard Dimensions	6"
Intended Use	On Water

Distributor Part Number	5685417;04088x30079
Sold as	1 each
Weight	185 lbs.
Composition	Boom - PVC Chain - Galvanized Steel
UNSPSC	24101907
Pigalog® Page Number	<u>Page 191</u>

Metric Equivalent

Dimensions	30m L x 45.7cm H
Weight	83.9 kg

Technical Information

Technical Documents

33 CFR 154.1040

40 CFR 112.7

40 CFR 122.26



One Pork Avenue • Tipton, PA 16684-0304

1-855-493-4647 • Fax: 1-800-621-7447 • newpig.com • hothogs@newpig.com