

## Simplex™ Boom

BOM107 For Moderate Current, 100' L x 18" H, 12" Draft Dimensions

Marine-grade aluminum connectors and a galvanized steel chain make this 5,000 lb. breaking strength non-absorbent floating boom great for containing oil spills and debris in moderate currents.

- Round, closed-cell polyethylene foam flotation cylinders corral liquids and debris up to 6" above water line
- Skirting barrier hangs 12" below the water line to keep pollutants from creeping under; galvanized steel chain runs the length of the boom to add weight and rigidity
- Heavy-duty, 22-ounce vinyl-coated polyester is UV resistant for regular outdoor use; welded, reinforced seams help ensure long life
- Marine-grade aluminum universal slide connectors and attached toggle pins permit linking of multiple units
- Polypropylene handle/anchor point eases handling and securing for easy deployment
- High-visibility yellow for instant recognition in emergencies
- Conforms to OPA-90 specifications
- Cleans easily using detergents, steam or power washing
- Light-weight and easy to move
- Add PIG Oil-Only Booms to absorb petroleum-based pollutants
- Need a custom boom? Call 1-800-HOT-HOGS (468-4647)



## Specifications

Break Strength	5,000 lb.
Style	Non-Absorbent Boom
Dimensions	100' L x 18" H
Application	Spill Response on Water
Brand	Elastec American Marine
Current Type	Moderate Current
Color	Yellow
Draft Dimensions	12"
Freeboard Dimensions	6"
Ideal For	Shorelines, Coastline

<b>Sold as</b>	1 each
<b>Weight</b>	185 lbs.
<b># per Pallet</b>	2
<b>Composition</b>	Boom: PVC Chain: Galvanized Steel
<b>UNSPSC</b>	24101907
<b>Pigalog® Page Number</b>	<u>Page 187</u>

## Metric Equivalent

<b>Weight</b>	83.9 kg
<b>Dimensions</b>	30m L x 46cm H

## Technical Information

### Technical Documents

33 CFR 154.1040

40 CFR 112.7

40 CFR 122.26



**One Pork Avenue • Tipton, PA 16684-0304**

1-855-493-4647 • Fax: 1-800-621-7447 • [newpig.com](http://newpig.com) • [hothogs@newpig.com](mailto:hothogs@newpig.com)