

Optimax II Boom

BOM119 For Strong Current, 50' x 20", 12" Draft Dimensions

Non-absorbent floating booms quickly contain oil spills and debris on rough, fast-flowing waters.

- Floating spill containment boom corrals liquids and debris while its skirting blocks pollutants underneath
- Vinyl-coated, UV-resistant polyester withstands up to 12-month deployment
- 6,400 lb. breaking strength
- Link multiple units using aluminum universal slide connectors
- Nylon handles allow single-person handling and anchoring
- Conforms to OPA-90 specs for protected water and fast currents in streams, rivers, estuaries and near-shore ocean
- Add PIG Oil-Only Booms to absorb petroleum-based pollutants
- Need a custom boom? Call 1-800-HOT-HOGS (468-4647)



Specifications

Style	Non-Absorbent Boom
Color	Yellow
Dimensions	50' L x 20" H
Brand	Elastec American Marine
Current Type	Strong Current
Intended Use	On Water
Sold as	1 each
Weight	110 lbs.
Composition	Skin - PVC Flotation - Polystyrene Chain - Galvanized Steel
Application	Spill Response
Draft Dimensions	12"
Freeboard Dimensions	8"
UNSPSC	24101907
Pigalog® Page Number	Page 191

Metric Equivalent

Dimensions	15m L x 50.8cm H
-------------------	------------------

Weight

49.9 kg

Technical Information

Technical Documents

33 CFR 154.1040

33 CFR 154.545(a)

40 CFR 112.7

40 CFR 122.26



New Pig

World's best stuff for leaks, drips and spills.

One Pork Avenue • Tipton, PA 16684-0304

1-855-493-4647 • Fax: 1-800-621-7447 • newpig.com • hothogs@newpig.com