

## Optimax II Boom

BOM119 For Strong Current, 50' x 20", 12" Draft Dimensions

Non-absorbent floating booms quickly contain oil spills and debris on rough, fast-flowing waters.

- Floating spill containment boom corrals liquids and debris while its skirting blocks pollutants underneath
- Vinyl-coated, UV-resistant polyester withstands up to 12-month deployment
- 6,400 lb. breaking strength
- Link multiple units using aluminum universal slide connectors
- Nylon handles allow single-person handling and anchoring
- Conforms to OPA-90 specs for protected water and fast currents in streams, rivers, estuaries and near-shore ocean
- Add PIG Oil-Only Booms to absorb petroleum-based pollutants
- Need a custom boom? Call 1-800-HOT-HOGS (468-4647)



### Specifications

Style	Non-Absorbent Boom
Dimensions	50' L x 20" H
Application	Spill Response
Brand	Elastec American Marine
Current Type	Strong Current
Draft Dimensions	12"
Color	Yellow
Freeboard Dimensions	8"
Intended Use	On Water
Distributor Part Number	6644113;04088x94185
Sold as	1 each
Weight	110 lbs.
# per Pallet	4
Composition	Skin - PVC Flotation - Polystyrene Chain - Galvanized Steel
UNSPSC	24101907
Pigalog® Page Number	<a href="#">Page 185</a>

### Metric Equivalent

**Dimensions**

15m L x 50.8cm H

**Weight**

49.9 kg

**Technical Information****Technical Documents**[33 CFR 154.1040](#)[33 CFR 154.545\(a\)](#)[40 CFR 112.7](#)[40 CFR 122.26](#)**New Pig**

World's best stuff for leaks, drips and spills.

**One Pork Avenue • Tipton, PA 16684-0304**1-855-493-4647 • Fax: 1-800-621-7447 • [newpig.com](http://newpig.com) • [hothogs@newpig.com](mailto:hothogs@newpig.com)