

















PIG® Oil-Only Absorbent Boom

BOM400 ext. dia. 8" x 10' L, Each absorbs up to 12 gal.,2 booms per bag

Confine and absorb oil and fuel spills on water.

- Absorbs and retains oils and oil-based liquids including lubricants and fuels - without taking in a drop of water
- Booms float at surface for easy retrieval, even when saturated
- Tough outer mesh is UV resistant for long-term outdoor use without degradation; lets fluids easily pass through to filler material
- Rope running along length of boom withstands up to 400-lb. loads, adding strength for deployment and retrieval
- Spunbond polypropylene skin is UV resistant up to 12 months; meets ANSI and MIL-SPEC standards for static decay
- Strong, zinc-plated carbon steel attachment clips and rings allow you to link booms together for greater length
- Bright white color makes booms easier to see in outdoor environments and clearly shows saturation level
- Can be incinerated after use to reduce waste or for fuels blending



Specifications

Sold as

Absorbency Range	20 - 29.9 gal.
Dimensions	ext. dia. 8" x 10' L
Absorbency	Up to 24 gal. per bag
Absorbency per	Up to 12 gal. per boom
Application	Spill Response on Water
Brand	PIG
Color	White
Clip/Ring	Zinc Plated Carbon Steel
Filler	Polypropylene
Fluid Absorbed	Oils; Fuels; Oil-Based Liquids (Not Water)
Skin/Outer Mesh	Skin - Polypropylene, Outer Mesh - Polyester

2 booms per bag

Weight	28 lbs.
# per Pallet	9
UNSPSC	47131907
Pigalog® Page Number	<u>Page 55</u>

Metric Equivalent

Absorbency per	Up to 45.4 L per boom
Absorbency	Up to 90.8 L per bag
Weight	12.7 kg

Dimensions ext. dia. 20cm x 3m L

Technical Information

Certifications, Approvals and Ratings

ANSI/ESD STM11.11,MIL-STD-3010C

Technical Documents

UV-Resistance Comparison Testing of Spunbond and Meltblown

Technical Data Sheet for PIG® Oil Only Absorbents

40 CFR 112.7

40 CFR 122.26



One Pork Avenue • Tipton, PA 16684-0304

1-855-493-4647 • Fax: 1-800-621-7447 • newpig.com • hothogs@newpig.com