



PIG® Oil-Only Absorbent Boom

BOM408 ext. dia. 5" x 20' L,Each absorbs up to 12 gal.,2 booms per bag

Confine and absorb oil and fuel spills on water.

- Absorbs and retains oils and oil-based liquids including lubricants and fuels - without taking in a drop of water
- Booms float at surface for easy retrieval, even when saturated
- Tough outer mesh is UV resistant for long-term outdoor use without degradation; lets fluids easily pass through to filler material
- Rope running along length of boom withstands up to 400-lb. loads, adding strength for deployment and retrieval
- Spunbond polypropylene skin is UV resistant up to 12 months; meets ANSI and MIL-SPEC standards for static decay
- Strong, zinc-plated carbon steel attachment clips and rings allow you to link booms together for greater length
- Bright white color makes booms easier to see in outdoor environments and clearly shows saturation level
- Can be incinerated after use to reduce waste or for fuels blending

pig	LCYCLES CONTENT	Autoship Eligible
EXCLUSIVE		

Specifications

Absorbency Range	20 - 29.9 gal.
Dimensions	ext. dia. 5" x 20' L
Recycled Content	98% Pre-Consumer Recycled Polypropylene Filler
Absorbency	Up to 24 gal. per bag
Absorbency per	Up to 12 gal. per boom
Application	Spill Response on Water
Color	White
Brand	PIG
Clip/Ring	Zinc Plated Carbon Steel
Filler	Polypropylene
Fluid Absorbed	Oils; Fuels; Oil-Based Liquids (Not Water)
Skin/Outer Mesh	Skin - Polypropylene, Outer Mesh - Polyester

Sold as	2 booms per bag		
Weight	21.28 lbs.		
# per Pallet	12		
UNSPSC	47131907		
Pigalog® Page Number	Page 55		
Metric Equivalent			
Absorbency per	Up to 45.4 L per boom		
Absorbency	Up to 90.8 L per bag		
Weight	9.7 kg		
Dimensions	ext. dia. 13cm x 6.1m L		
Technical Information			
Certifications, Approvals and Ratings			
ANSI/ESD STM11.11,MIL-STD-3010C			
Technical Documents			
UV-Resistance Comparison Testing of Spunbond and Meltblown			
Spill Response Training: Absorbent Booms			
Instructions for Using PIG® Absorbent Booms			
Technical Data Sheet for PIG® Oil Only Absorbents			
40 CFR 112.7			
40 CFR 122.26			



World's best stuff for leaks, drips and spills. 1-855-493-4

One Pork Avenue • Tipton, PA 16684-0304

1-855-493-4647 • Fax: 1-800-621-7447 • newpig.com • hothogs@newpig.com