

## PIG® Oil-Only Absorbent Boom

BOM408 ext. dia. 5" x 20' L, Each absorbs up to 12 gal., 2 booms per bag



Confine and absorb oil and fuel spills on water.

- Absorbs and retains oils and oil-based liquids - including lubricants and fuels - without taking in a drop of water
- Booms float at surface for easy retrieval, even when saturated
- Tough outer mesh is UV resistant for long-term outdoor use without degradation; lets fluids easily pass through to filler material
- Rope running along length of boom withstands up to 400-lb. loads, adding strength for deployment and retrieval
- Spunbond polypropylene skin is UV resistant up to 12 months; meets ANSI and MIL-SPEC standards for static decay
- Strong, zinc-plated carbon steel attachment clips and rings allow you to link booms together for greater length
- Bright white color makes booms easier to see in outdoor environments and clearly shows saturation level
- Can be incinerated after use to reduce waste or for fuels blending



### Specifications

<b>Absorbency Range</b>	20 - 29.9 gal.
<b>Dimensions</b>	ext. dia. 5" x 20' L
<b>Recycled Content</b>	98% Pre-Consumer Recycled Polypropylene Filler
<b>Absorbency</b>	Up to 24 gal. per bag
<b>Absorbency per</b>	Up to 12 gal. per boom
<b>Application</b>	Spill Response on Water
<b>Color</b>	White
<b>Brand</b>	PIG
<b>Clip/Ring</b>	Zinc Plated Carbon Steel
<b>Filler</b>	Polypropylene
<b>Fluid Absorbed</b>	Oils; Fuels; Oil-Based Liquids (Not Water)
<b>Skin/Outer Mesh</b>	Skin - Polypropylene, Outer Mesh - Polyester

<b>Sold as</b>	2 booms per bag
<b>Weight</b>	21.28 lbs.
<b># per Pallet</b>	12
<b>UNSPSC</b>	47131907
<b>Pigalog® Page Number</b>	<u>Page 55</u>

## Metric Equivalent

<b>Absorbency per</b>	Up to 45.4 L per boom
<b>Absorbency</b>	Up to 90.8 L per bag
<b>Weight</b>	9.7 kg
<b>Dimensions</b>	ext. dia. 13cm x 6.1m L

## Technical Information

### Certifications, Approvals and Ratings

ANSI/ESD STM11.11,MIL-STD-3010C

### Technical Documents

[UV-Resistance Comparison Testing of Spunbond and Meltblown](#)

[Spill Response Training: Absorbent Booms](#)

[Instructions for Using PIG® Absorbent Booms](#)

[Technical Data Sheet for PIG® Oil Only Absorbents](#)

[40 CFR 112.7](#)

[40 CFR 122.26](#)



**One Pork Avenue • Tipton, PA 16684-0304**

1-855-493-4647 • Fax: 1-800-621-7447 • [newpig.com](http://newpig.com) • [hothogs@newpig.com](mailto:hothogs@newpig.com)