


PIG® Sheen Clean® Oil-Only Boom

BOM600 5" x 10', Absorbs up to 6 gal. per boom, 4 booms

Cleans up the thin, oily residue floating on large bodies of water that other absorbents leave behind.

- Proprietary filler blends high-capacity recycled cellulose with a copolymer that pulls in thin, filmy sheens of oil
- Ideal for long-term deployment to remove sheen after oil-based spills or absorb oil residue on large bodies of water; also effective in retention ponds, catch basins and tanks
- Tough outer mesh is UV resistant for long-term outdoor use without degradation; lets fluids easily pass through to filler material
- Rope running along length of boom withstands up to 400-lb. loads, adding strength for deployment and retrieval
- Spunbond polypropylene skin is UV resistant up to 12 months; meets ANSI and MIL spec standards for static decay
- Absorbs and retains oils and oil-based liquids - including lubricants and fuels - without taking in a drop of water
- Durable steel clips and rings allow you to link booms together
- Not recommended for use with acids, bases or other corrosive liquids



Specifications

Fluid Absorbed	Oils, Fuels, Other Oil-Based Liquids Only
Color	White
Dimensions	ext. dia. 5" x 10' L
Recycled Content	90% Post-Consumer Recycled Cellulose Waste
Absorbency	Up to 24 gal. per bag
Absorbency per	Up to 6 gal. per boom
Brand	PIG
Filler	Hydrophobic Cellulose & Copolymer Proprietary Blend
Skin/Outer Mesh	Skin - Polypropylene
Sold as	4 booms per bag
Weight	30 lbs.

# per Pallet	12
Application	Skimming
UNSPSC	47131907
Pigalog® Page Number	<u>Page 57</u>

Metric Equivalent

Absorbency per	Up to 22.7 L per boom
Absorbency	Up to 90.8 L per bag
Dimensions	ext. dia. 12.7cm x 3m L
Weight	13.6 kg

Technical Information

Certifications, Approvals and Ratings

ANSI/ESD STM11.11,MIL-STD-3010C

Technical Documents

[UV-Resistance Comparison Testing of Spunbond and Meltblown](#)

[Spill Response Training: Absorbent Booms](#)

[PIG® Sheen Clean® Oil-Only Absorbents](#)

[40 CFR 112.7](#)

[40 CFR 122.26](#)

Disclaimers

[Corrosive Liquids Notice](#)

Not recommended for acids, bases or other corrosive liquids.



One Pork Avenue • Tipton, PA 16684-0304

1-855-493-4647 • Fax: 1-800-621-7447 • newpig.com • hothogs@newpig.com