

Justrite® Corrosives Safety Cabinet



CAB7580 Self-Closing Door Style, Holds 45 gal., 43" W x 18" D x 65" H

Handle your corrosives with care by securing them in a Justrite Corrosives Safety Cabinet.

- Polyethylene liners for shelves and sill resist acids, bases and pesticides
- Ribbed liner design helps keep containers out of contact with accumulated liquids
- FM Approved for storage of flammables; also meets NFPA and OSHA specifications
- Fully MIG-welded 18-gauge steel construction is built for a lifetime of continuous use
- Three-point stainless steel bullet latch provides fail-safe, positive door closure; stands up to high heat and harsh use
- Recessed handle won't catch on passing traffic
- True double-wall construction with 1.5" of insulating air space provides excellent fire protection
- 2" leakproof sump contains leaks, drips and spills
- Welded hangers interlock with shelf for maximum stability; no brackets required
- Shelf provides 350 lb. UDL weight capacity when evenly loaded
- Built-in ground connector inhibits static buildup
- Powder coated finish, inside and out, resists chemicals, rust and corrosion
- Self-closing mechanism makes sure doors shut completely every time
- Fusible link lets you prop doors open; melts at 165 degrees F to automatically shut doors in case of fire



Specifications

Use With	Corrosive Chemicals
Dimensions	43" W x 18" D x 65" H
Brand	Justrite
Capacity	45 gal.
Category	Corrosives Cabinet
Door Style	Self-Closing

Color	Blue
Interior Dimensions	39.5" W x 14.6" D x 60.5" H
Locking Mechanism	Keyed (2 Included)
Number of Shelves	2
Shelves	Adjustable
Special Feature	3 Tray Liners Included
Use With Flammables	Yes
Sold as	1 each
Weight	272.5 lbs.
# per Pallet	2
Composition	Cabinet - Steel Shelf - Galvanized Steel Tray Liner - Polyethylene
UNSPSC	24112402

Metric Equivalent

Weight	123.6 kg
Dimensions	109cm W x 46cm D x 165cm H

Technical Information

CountryNoShip

This product is subject to export restrictions and cannot be shipped to Australia or New Zealand.

Certifications, Approvals and Ratings

FM Approved,NFPA Code 30

Technical Documents

29 CFR 1910.106(d)(3)



One Pork Avenue • Tipton, PA 16684-0304
1-855-493-4647 • Fax: 1-800-621-7447• newpig.com • hothogs@newpig.com