

Bolt & Ring Open-Head UN Rated Steel Salvage Drum



DRM1001 Storage Capacity 85 gal., UN1A2/X440/S, UN1A2T/Y320/S, Thickness 1.2/1.2/1.2 mm

Ship damaged or leaking containers of hazardous materials in these UN Rated, open top steel salvage drums.

- UN Rated and tested to help ensure safe shipping of hazardous materials
- Open-head design and removable lid offer full, convenient access
- 12-gauge bolt ring closure, EPDM gasket and plated bolt/nut provide tight seal
- Interior is coated with a corrosion inhibitor; choose optional phenolic/epoxy lining for added resistance
- High-visibility yellow with red multi-lingual "Salvage Drum" markings clearly identify drum
- 18-gauge steel lid, body and bottom meet strict wall thickness requirements to ensure strength, durability and long life

Item#	Description	Dimensions	Weight
DRM1001-LD	Lined	ext. dia. 26.56" x 39" H	63 lbs.
DRM1001-ULD	Unlined	ext. dia. 26.56" x 39" H	63 lbs.

Metric Equivalent:

Item#	Description	Dimensions	Weight
DRM1001-LD	Lined	ext. dia. 67cm x 99cm H	28.6 kg
DRM1001-ULD	Unlined	ext. dia. 67cm x 99cm H	28.6 kg

Specifications

Dimensions	ext. dia. 26.56" x 39" H
Storage Capacity	85 gal.
Brand	Skolnik
Bung Type	No Bung Holes
Drum Type	New Steel Drum
Interior Dimensions	26" Dia. x 37" H
Color	Red/Yellow
Lid Type	Open-Head - Nut & Bolt Ring
Lining	Lined
Thickness	1.2/1.2/1.2 mm

Sold as	1 each
Weight	63 lbs.
# per Pallet	6
Composition	Drum - 18-Gauge Steel Bolt Ring - 12-Gauge Steel Gasket - EPDM
UNSPSC	24112108
Pigalog® Page Number	<u>Page 300</u>

Metric Equivalent

Dimensions	ext. dia. 67cm x 99cm H
Storage Capacity	321.7 L
Weight	28.6 kg

Technical Information

Certifications, Approvals and Ratings

UN1A2/X440/S, UN1A2T/Y320/S

Technical Documents

49 CFR 173.3(c)(1)



One Pork Avenue • Tipton, PA 16684-0304

1-855-493-4647 • Fax: 1-800-621-7447 • newpig.com • hothogs@newpig.com