

Ayling & Reichert Stainless Steel Piston Hand Drum Pump

DRM1109 Ideal For Acids; Alcohol; Coolants; Solvents, Max Flow Rate 8 oz./Stroke, Max Viscosity 40 wt.

Built-in grounding clips let you pump drums of acetic acid (20%-50%), alcohol, butyl acetate, calcium hydroxide (10%-20%, boiling), chromic acid (5%-10%), denatured alcohol, ethylene glycol, heptane, lacquer thinner, nitric acid (10%-50%) or toluene.

- FM Approved drum pump helps improve safety of handling flammable and combustible liquids
- Built-in bonding and grounding wires with clips help control static electricity to prevent sparking
- Bonding/grounding apparatus stays attached and visible, encouraging use during transfer of flammable liquids
- Internal flame arrestor helps prevent flashback
- PTFE piston, packing gland and gasket offer exceptional resistance to chemicals and solvents
- Stainless steel construction makes entire pump resist aggressive chemicals
- T-handle design and piston action make pump easy to operate
- Includes 2" bung adapter for a secure fit on 15- to 55-gallon drums



Specifications

Use With	15 to 55 gal. Drum w/ 2" NPT Bung
Brand	Ayling & Reichert
Compatible With	Alcohol; Butyl Acetate; Ethylene Glycol; Heptane; Lacquer Thinner; Nitric Acid (10%-50%); Toluene
Ideal For	Acids; Alcohol; Coolants; Solvents
Manual Pump Type	Piston Operated
Max Flow Rate	8 oz./Stroke
Color	Silver
Max Viscosity	40 wt.
Powered By	Manual
Use With Flammables	Yes

Sold as	1 each
Weight	4 lbs.
Composition	Body Head, Body Assembly, Bung Adapter, Extension Tube, Handle, Packing Nut: 316 Stainless Steel Bonding, Grounding Wires: Copper End Plug Assembly: 316 Stainless Steel, Glass
Includes	1 - Pump 1 - 2" Adapter 1 - Tube
UNSPSC	40151529
Pigalog® Page Number	<u>Page 333</u>

Metric Equivalent

Weight	1.8 kg
---------------	--------

Technical Information

Certifications, Approvals and Ratings

FM Approved

Technical Documents

[Stainless Steel Component for Pump](#)

[Teflon Component for Pump](#)

[Pump Selection Guide](#)



One Pork Avenue • Tipton, PA 16684-0304

1-855-493-4647 • Fax: 1-800-621-7447 • newpig.com • hothogs@newpig.com