

# Ayling & Reichert Stainless Steel Piston Hand Drum Pump

DRM1109 For Alcohol; Butyl Acetate; Ethylene Glycol; Heptane; Lacquer Thinner; Nitric Acid (10%-50%); Toluene, Max Flow Rate 8 oz./Stroke, Max Viscosity 40 wt.

Built-in grounding clips let you pump drums of acetic acid (20%-50%), alcohol, butyl acetate, calcium hydroxide (10%-20%, boiling), chromic acid (5%-10%), denatured alcohol, ethylene glycol, heptane, lacquer thinner, nitric acid (10%-50%) or toluene.

- FM Approved drum pump helps improve safety of handling flammable and combustible liquids
- Built-in bonding and grounding wires with clips help control static electricity to prevent sparking
- Bonding/grounding apparatus stays attached and visible, encouraging use during transfer of flammable liquids
- Internal flame arrestor helps prevent flashback
- PTFE piston, packing gland and gasket offer exceptional resistance to chemicals and solvents
- Stainless steel construction makes entire pump resist aggressive chemicals
- T-handle design and piston action make pump easy to operate
- Includes 2" bung adapter for a secure fit on 15- to 55-gallon drums



## Specifications

<b>Max Flow Rate</b>	8 oz./Stroke
<b>Max Viscosity</b>	40 wt.
<b>Use With</b>	15 to 55 gal. Drum w/ 2" NPT Bung
<b>Color</b>	Silver
<b>Brand</b>	Ayling & Reichert
<b>Compatible With</b>	Alcohol; Butyl Acetate; Ethylene Glycol; Heptane; Lacquer Thinner; Nitric Acid (10%-50%); Toluene
<b>Manual Pump Type</b>	Piston Operated
<b>Powered By</b>	Manual
<b>Use With Flammables</b>	Yes

<b>Sold as</b>	1 each
<b>Weight</b>	4 lbs.
<b># per Pallet</b>	392
<b>Composition</b>	Body Head, Body Assembly, Bung Adapter, Extension Tube, Handle, Packing Nut - 316 Stainless Steel Bonding/Grounding Wires - Copper End Plug Assembly - 316 Stainless Steel/Glass
<b>Includes</b>	1 - Pump 1 - 2" Adapter 1 - Tube
<b>UNSPSC</b>	40151529
<b>Pigalog® Page Number</b>	<u>Page 327</u>

## Metric Equivalent

<b>Weight</b>	1.8 kg
---------------	--------

## Technical Information

### Certifications, Approvals and Ratings

FM Approved

### Technical Documents

[Stainless Steel Component for Pump](#)

[Teflon Component for Pump](#)

[Pump Selection Guide](#)



**One Pork Avenue • Tipton, PA 16684-0304**

1-855-493-4647 • Fax: 1-800-621-7447 • [newpig.com](http://newpig.com) • [hothogs@newpig.com](mailto:hothogs@newpig.com)