

## Zee Line Air-Operated Double Diaphragm Transfer Pump

DRM1284 For Motor Oil; Waste Oil; ATF, Max Flow Rate 14 gal./Minute

Move waste oil quickly and easily with this aluminum-base transfer pump.

- Flow rate is up to 14 gallons per minute (GPM)
- Aluminum base with polypropylene center section pump; 3/4" NPT inlet and outlet pumps, Buna-N diaphragm, acetal balls and aluminum seats
- For use with waste oil, gear lube and automatic transmission fluid (ATF)
- Non-stalling and lube-free
- Bolt pattern of 3.25" x 4.37" and stands 10.25"H



### Specifications

<b>Use With</b>	Waste Oil Pump System
<b>Air Line Input Fitting</b>	.25" Air Line Fitting
<b>Brand</b>	Zeeline
<b>Compatible With</b>	Motor Oil; Waste Oil; ATF
<b>Explosion Proof</b>	No
<b>Ideal For</b>	Oils
<b>Color</b>	White
<b>Max Flow Rate</b>	14 gal./Minute
<b>Max Viscosity</b>	1735 CentiPoise
<b>Powered By</b>	Air
<b>Power Requirements</b>	100 PSI @ 16 CFM
<b>Use With Flammables</b>	No
<b>Sold as</b>	1 each
<b>Weight</b>	15 lbs.

## Composition

Body: Aluminum, Polypropylene

Diaphragm: Buna N

Balls: Acetal

Seats: Aluminum

UNSPSC

40151529

## Metric Equivalent

Weight

6.8 kg

## Technical Information

### USOnly

This product can ONLY be shipped to the United States.

## Technical Documents

[Pump Selection Guide](#)



**New Pig**

World's best stuff for leaks, drips and spills.

**One Pork Avenue • Tipton, PA 16684-0304**

1-855-493-4647 • Fax: 1-800-621-7447 • [newpig.com](http://newpig.com) • [hothogs@newpig.com](mailto:hothogs@newpig.com)