# Zee Line Air-Operated Double Diaphragm Transfer Pump

DRM1285 Ideal For Oils,Max Flow Rate 37 gal./Minute

Move waste oil quickly and easily with this aluminum-body transfer pump.

- Flow rate is up to 37 gallons per minute (GPM)
- All-aluminum body with polypropylene center section pump; 1" NPT inlet and outlet pumps, Buna-N diaphragm, acetal balls and aluminum seats
- For use with waste oil, gear lube and automatic transmission fluid (ATF)
- Non-stalling and lube-free
- Bolt pattern of 4.25" x 8.25" and stands 14.125"H

## Specifications

| | |
|---|---|
| **Use With** | Waste Oil Pump System |
| **Air Line Input Fitting** | .25" Air Line Fitting |
| **Brand** | Zeeline |
| **Compatible With** | Motor Oil; Waste Oil; ATF |
| **Explosion Proof** | No |
| **Ideal For** | Oils |
| **Color** | White |
| **Max Flow Rate** | 37 gal./Minute |
| **Max Viscosity** | 1735 CentiPoise |
| **Powered By** | Air |
| **Power Requirements** | 80 PSI @ 40 CFM |
| **Use With Flammables** | No |
| **Sold as** | 1 each |
| **Weight** | 16 lbs. |

| | |
|---|---|
| **Composition** | Body: Aluminum, Polypropylene<br>Diaphragm: Buna N<br>Balls: Acetal<br>Seats: Aluminum |
| **UNSPSC** | 40151529 |

## Metric Equivalent

| | |
|---|---|
| **Weight** | 7.3 kg |

## Technical Information

| |
|---|
| **USOnly** |

This product can ONLY be shipped to the United States.

**Technical Documents**

Pump Selection Guide

New Pig
World's best stuff for leaks, drips and spills.

**One Pork Avenue • Tipton, PA 16684-0304**
1-855-493-4647 • Fax: 1-800-621-7447• newpig.com • hothogs@newpig.com