

Zee Line Air-Operated Double Diaphragm Transfer Pump System

DRM1288 For Motor Oil; Waste Oil; ATF, Max Flow Rate 37 gal./Minute

Move waste oil quickly and easily with this aluminum-body transfer pump and system components.

- Flow rate is up to 37 gallons per minute (GPM)
- All-aluminum body with polypropylene center section pump; 1" NPT inlet and outlet pumps, Buna-N diaphragm and hoses, acetal balls and aluminum seats
- For use with waste oil, gear lube and automatic transmission fluid (ATF)
- Non-stalling and lube-free
- System includes male and female cam locks, brass ball valves, hydraulic adapter swivel, street elbow, suction hose, discharge hose, nipple, strainer, airline filter and reducer bushing
- Mounting bracket lets you install pump on a wall, table or cart near your transfer station
- Pump has bolt pattern of 4.25" x 8.25" and stands 14.125"H



Specifications

Use With	Waste Oil Pump System
Brand	Zeeline
Compatible With	Motor Oil; Waste Oil; ATF
Explosion Proof	No
Ideal For	Oils
Max Flow Rate	37 gal./Minute
Color	Black/Red/White
Max Viscosity	140 wt.
Powered By	Air
Power Requirements	80 PSI @ 40 CFM
Speed	Single Speed
Use With Flammables	No
Sold as	1 each
Weight	35 lbs.

Composition

Body - Aluminum and Polypropylene
Diaphragm - Buna N
Balls - Acetal
Seats - Aluminum
Valves - Brass
Elbow - Galvanized
Nipples - Galvanized
Hoses - Buna N

Includes

1 - Double Diaphragm Pump (DRM1285)
1 - 3/4" Male Camlock
1 - 3/4" Female Camlock
3 - 3/4" Brass Ball Valve
2 - 1/2" x 3/4" Hydraulic Adapter Swivel
1 - 3/4" Galvanized Steel Street L
1 - 3/4" x 8' Suction Hose
1 - 3/4" x 8' Discharge Hose
2 - 3/4" x 2" Nipple
1 - 3/4" Strainer
1 - Wall Mount Bracket
1 - Airline Filter
1 - Reducer Bushing

UNSPSC

40151529

Pigalog® Page NumberPage 323**Metric Equivalent****Weight**

15.9 kg

Technical Information**Technical Documents****Pump Selection Guide****One Pork Avenue • Tipton, PA 16684-0304**1-855-493-4647 • Fax: 1-800-621-7447 • newpig.com • hothogs@newpig.com