

Fill-Rite Polypropylene Piston Hand Drum Pump

DRM1289 For DEF; Engine Oils; Antifreeze; Hydraulic Oils; Degreaser, Max Flow Rate 11 oz./Stroke, Max Viscosity 40 wt.

Transfer Diesel Exhaust Fluid (DEF) easily and economically with a hand-operated, piston-style pump.

- Can also be used with compatible chemicals like antifreeze, hydraulic oils, engine and gear oils and degreasers
- Pump design uses materials that will not taint or alter the chemical structure of the DEF being transferred
- Maximum flow rate is 11 oz. per stroke
- Fits 15- to 55-gallon drum with a 2" NPT bung



Specifications

Use With	15 to 55 gal. Drum w/ 2" NPT Bung
Brand	Fill-Rite
Compatible With	DEF; Engine Oils; Antifreeze; Hydraulic Oils; Degreaser
Ideal For	Coolants; General-Purpose Chemicals; Oils
Manual Pump Type	Piston Operated
Max Flow Rate	11 oz./Stroke
Color	Blue
Max Viscosity	40 wt.
Powered By	Manual
Use With Flammables	No
Sold as	1 each
Weight	4 lbs.
# per Pallet	120

Composition

Body: Polypropylene
Valves: Polypropylene
Inlet Screen: Stainless Steel
O-rings: Fluorocarbon

UNSPSC

40151529

Pigalog® Page Number

Page 321

Metric Equivalent

Weight

1.8 kg

Technical Information

Technical Documents

Pump Selection Guide



New Pig

World's best stuff for leaks, drips and spills.

One Pork Avenue • Tipton, PA 16684-0304

1-855-493-4647 • Fax: 1-800-621-7447 • newpig.com • hothogs@newpig.com