

Wesco Aluminum Rotary Hand Drum Pump - Non-Sparking

DRM1311 For Gasoline; Kerosene; Antifreeze, Max Flow Rate 8 oz./Revolution, Max Viscosity 60 wt.

Use this self-priming, non-sparking hand drum pump to safely pump oils and noncorrosive liquids.

- Sturdy aluminum construction and phenolic vaning
- Compatible with gasoline, kerosene and antifreeze, with a maximum 60 wt. viscosity
- Dispenses up to 8 oz./revolution
- Manual pump is rotary-operated
- Use with any 15 to 55 gal. drum with 2" NPT bung
- Must be used with a ground wire



Specifications

Use With	15 to 55 gal. Drum w/ 2" NPT Bung
Brand	Wesco
Compatible With	Gasoline; Kerosene; Antifreeze
Ideal For	Coolants; Fuel
Manual Pump Type	Rotary Operated
Max Flow Rate	8 oz./Revolution
Color	Silver
Max Viscosity	60 wt.
Powered By	Manual
Use With Flammables	Yes
Sold as	1 each
Weight	8.17 lbs.
# per Pallet	180
Composition	Body: Aluminum Vanes: Phenolic
UNSPSC	40151529

Metric Equivalent

Weight

3.7 kg

[Technical Information](#)

[Technical Documents](#)

[Pump Selection Guide](#)



New Pig

World's best stuff for leaks, drips and spills.

One Pork Avenue • Tipton, PA 16684-0304

1-855-493-4647 • Fax: 1-800-621-7447 • newpig.com • hothogs@newpig.com