

## Action Pump FDA-Compliant 55 Gal. Piston Drum Pump

DRM1317 For Food Products; Lubricants; Oils; High Viscosity Fluids; Mild Acids, Max Flow Rate 15 oz./Stroke, Max Viscosity 8,800 CentiPoise

FDA Compliant piston pump easily dispenses viscous liquids and harsh chemicals from 55-gallon drums.

- FDA Compliant pump is made from polypropylene with polyethylene wetted materials
- Food-grade pump is ideal for dispensing thick liquids such as olive oils, syrups and honey; also compatible with a wide range of chemicals including sanitizers, acids, bases, glycerine, caustics, chlorines, crop chemicals, diesel and liquid fertilizer
- Manual pump is more affordable than electric or air-powered pumps, and can be used even when power supplies are not available
- Handles liquids up to 140°F at a maximum viscosity of 8,800 cP; moves up to 15 ounces per stroke
- Unique collar design fits both 2" NPT and 2" buttress bungs
- Attach 1" diameter hose (not included) onto spout for dispensing at a distance
- Safety strap "locks out" the pump to help reduce waste
- Spout can be rotated to eliminate messy drips



### Specifications

<b>Max Flow Rate</b>	15 oz./Stroke
<b>Max Viscosity</b>	8,800 CentiPoise
<b>Use With</b>	55 gal. Drum w/ 2" NPT or 2" Buttress Bung
<b>Color</b>	White
<b>Brand</b>	Action Pump
<b>Compatible With</b>	Food Products; Lubricants; Oils; High Viscosity Fluids; Mild Acids
<b>Manual Pump Type</b>	Piston Operated
<b>Powered By</b>	Manual
<b>Temperature Limit</b>	140°F (60°C) Maximum Temperature
<b>Use With Flammables</b>	No
<b>Sold as</b>	1 each

<b>Weight</b>	1.4 lbs.
<b># per Pallet</b>	60
<b>Composition</b>	Body - Polypropylene Piston - Polyethylene
<b>UNSPSC</b>	40151529
<b>Pigalog® Page Number</b>	<u>Page 328</u>
<b>Metric Equivalent</b>	
<b>Weight</b>	.6 kg

### Technical Information



**One Pork Avenue • Tipton, PA 16684-0304**

1-855-493-4647 • Fax: 1-800-621-7447 • [newpig.com](http://newpig.com) • [hothogs@newpig.com](mailto:hothogs@newpig.com)