



## Action Pump FDA-Compliant 55 Gal. Piston Drum Pump

DRM1317 For Food Products; Lubricants; Oils; High Viscosity Fluids; Mild Acids, Max Flow Rate 15 oz./Stroke, Max Viscosity 8,800 CentiPoise

FDA Compliant piston pump easily dispenses viscous liquids and harsh chemicals from 55-gallon drums.

- FDA Compliant pump is made from polypropylene with polyethylene wetted materials
- Food-grade pump is ideal for dispensing thick liquids such as olive oils, syrups and honey; also compatible with a wide range of chemicals including sanitizers, acids, bases, glycerine, caustics, chlorines, crop chemicals, diesel and liquid fertilizer
- Manual pump is more affordable than electric or air-powered pumps, and can be used even when power supplies are not available
- Handles liquids up to 140°F at a maximum viscosity of 8,800 cP; moves up to 15 ounces per stroke
- Unique collar design fits both 2" NPT and 2" buttress bungs
- Attach 1" diameter hose (not included) onto spout for dispensing at a distance
- Safety strap "locks out" the pump to help reduce waste
- Spout can be rotated to eliminate messy drips



### Specifications

|                            |                                                                    |
|----------------------------|--------------------------------------------------------------------|
| <b>Use With</b>            | 55 gal. Drum w/ 2" NPT or 2" Buttress Bung                         |
| <b>Brand</b>               | Action Pump                                                        |
| <b>Compatible With</b>     | Food Products; Lubricants; Oils; High Viscosity Fluids; Mild Acids |
| <b>Ideal For</b>           | Acids; Bases; Food Grade Liquids; Oils                             |
| <b>Manual Pump Type</b>    | Piston Operated                                                    |
| <b>Max Flow Rate</b>       | 15 oz./Stroke                                                      |
| <b>Color</b>               | White                                                              |
| <b>Max Viscosity</b>       | 8,800 CentiPoise                                                   |
| <b>Powered By</b>          | Manual                                                             |
| <b>Temperature Limit</b>   | 140°F (60°C) Maximum Temperature                                   |
| <b>Use With Flammables</b> | No                                                                 |

|                             |                                               |
|-----------------------------|-----------------------------------------------|
| <b>Sold as</b>              | 1 each                                        |
| <b>Weight</b>               | 1.4 lbs.                                      |
| <b># per Pallet</b>         | 60                                            |
| <b>Composition</b>          | Body - Polypropylene<br>Piston - Polyethylene |
| <b>UNSPSC</b>               | 40151529                                      |
| <b>Pigalog® Page Number</b> | <u>Page 322</u>                               |

## Metric Equivalent

|               |       |
|---------------|-------|
| <b>Weight</b> | .6 kg |
|---------------|-------|

## Technical Information

### Technical Documents

[Pump Selection Guide](#)



**One Pork Avenue • Tipton, PA 16684-0304**

1-855-493-4647 • Fax: 1-800-621-7447 • [newpig.com](http://newpig.com) • [hothogs@newpig.com](mailto:hothogs@newpig.com)