

## 30-Gallon Tight-Head UN Rated Steel Drum

DRM1426 Storage Capacity 30 gal.,UN1A1/X1.8/300,Thickness 1.5/0.9/1.5 mm

Tough, UN Rated drums are made for hazardous materials, so you can rely on them to deliver safety and compliance.

- UN Rated for Packing Groups I, II and II and tested to help ensure safe shipping of hazardous materials
- Tight-head design is equipped with 2" NPT and 3/4" NPT bungs
- Interior is coated with a corrosion inhibitor; choose optional phenolic/epoxy lining for added resistance
- Steel top, bottom and body meet strict wall thickness requirements to ensure strength, durability and long life



Item#	Description	Dimensions	Weight
DRM1426-LD	Lined	ext. dia. 19.25" x 29.5" H	31 lbs.
DRM1426-ULD	Unlined	ext. dia. 19.25" x 29.5" H	31 lbs.

### Metric Equivalent:

Item#	Description	Dimensions	Weight
DRM1426-LD	Lined	ext. dia. 49cm x 75cm H	14.1 kg
DRM1426-ULD	Unlined	ext. dia. 49cm x 75cm H	14.1 kg

### Specifications

Dimensions	ext. dia. 19.25" x 29.5" H
Storage Capacity	30 gal.
Brand	Skolnik
Bung Type	2" NPT and .75" NPT (Tri-Sure) Bungs
Drum Type	New Steel Drum
Interior Dimensions	18.75" Dia. x 29" H
Color	Black
Lid Type	Tight-Head
Lining	Lined; Unlined
Thickness	1.5/0.9/1.5 mm
Sold as	1 each
Weight	31 lbs.
# per Pallet	15

## Composition

Drum: Steel  
Lining: Phenolic Epoxy  
Gasket: Buna-N

## UNSPSC

24112108

## Pigalog® Page Number

Page 307

## Metric Equivalent

### Storage Capacity

113.6 L

### Weight

14.1 kg

### Dimensions

ext. dia. 49cm x 75cm H

## Technical Information

### USOnly

This product can ONLY be shipped to the United States.

## Certifications, Approvals and Ratings

UN1A1/X1.8/300



# New Pig

World's best stuff for leaks, drips and spills.

**One Pork Avenue • Tipton, PA 16684-0304**

1-855-493-4647 • Fax: 1-800-621-7447 • [newpig.com](http://newpig.com) • [hothogs@newpig.com](mailto:hothogs@newpig.com)