

55-Gallon Tight-Head UN Rated Steel Drum

DRM1427 Storage Capacity 55 gal., UN1A1/X1.8/300, 1.1/0.8/1.1 mm

Tough, UN Rated drums are made for hazardous materials, so you can rely on them to deliver safety and compliance.

- UN Rated and tested to help ensure safe shipping of hazardous materials
- Tight-head design is equipped with 2" NPT and 3/4" NPT bungs
- Choose optional phenolic/epoxy lining for added corrosion resistance
- Steel lid, body and bottom meet strict wall thickness requirements to ensure strength, durability and long life



Item#	Description	Dimensions	Weight
DRM1427-BK-LD	Lined	ext. dia. 23" x 35.25" H	
DRM1427-BKW-ULD	Unlined	ext. dia. 23" x 35.25" H	

Metric Equivalent:

Item#	Description	Dimensions	Weight
DRM1427-BK-LD	Lined	ext. dia. 58.4cm x 89.5cm H	
DRM1427-BKW-ULD	Unlined	ext. dia. 58.4cm x 89.5cm H	

Specifications

Dimensions	ext. dia. 23" x 35.25" H
Storage Capacity	55 gal.
Bung Type	2" NPT and .75" NPT (Tri-Sure) Bungs
Drum Type	New Steel Drum
Interior Dimensions	22.5" Dia. x 33" H
Lid Type	Tight-Head
Lining	Lined; Unlined
Thickness	1.1/0.8/1.1 mm
Distributor Part Number	76183-706
Sold as	1 each
# per Pallet	8
Composition	Drum - Carbon Steel Bung Gasket - Buna-N Lining - Phenolic Epoxy
UNSPSC	24112108

Metric Equivalent

Dimensions	ext. dia. 58.4cm x 89.5cm H
-------------------	-----------------------------

Storage Capacity	208.2 L
-------------------------	---------

Technical Information

Certifications, Approvals and Ratings

UN1A1/X1.8/300



New Pig

World's best stuff for leaks, drips and spills.

One Pork Avenue • Tipton, PA 16684-0304

1-855-493-4647 • Fax: 1-800-621-7447 • newpig.com • hothogs@newpig.com