

FTI .33 HP Electric Pump Motor



DRM1887 For Medium Viscosities in Non-Explosive Areas; Corrosives, Max Flow Rate 10 gal./Minute, 115V/60 Hz

An excellent all-around pump for use with a wide range of tubes and liquids.

- Versatile .33 HP motor is rated continuous duty for general light- to medium-viscosity jobs
- Digital display provides easy monitoring of pump activity
- Use with FTI Pick-Up Tube; also compatible with FTI Drum Mixer (sold separately)
- Pick-Up Tube not included

Specifications

Brand	Finish Thompson
Compatible With	Medium Viscosities in Non-Explosive Areas; Corrosives
Explosion Proof	No
Horsepower	.33
Max Flow Rate	10 gal./Minute
Max Viscosity	500 CentiPoise
Color	Gray
Power Cord	12' w/ Plug
Powered By	Electric
Power Requirements	115V/60 Hz
Speed	Dual Speed
Use With Flammables	No
Sold as	1 each
Weight	14.7 lbs.
# per Pallet	36
Composition	Steel & Plastic
UNSPSC	40151529

Metric Equivalent

Weight	6.7 kg
--------	--------

Technical Information

Certifications, Approvals and Ratings

QPS Approved

Technical Documents

FTI Pumps

Pump Selection Guide



New Pig

World's best stuff for leaks, drips and spills.

One Pork Avenue • Tipton, PA 16684-0304

1-855-493-4647 • Fax: 1-800-621-7447 • newpig.com • hothogs@newpig.com