



55-Gallon Open-Head UN Rated Steel Drum

DRM423 55 gal., UN1A2/X435/S,
UN1A2/Y1.5/150, 1.2/1.2/1.2 mm

Tough, UN Rated open top drums are made for hazardous materials, so you can rely on them to deliver safety and compliance.

- UN Rated and tested to help ensure safe shipping of hazardous materials
- Open-head design and removable lid offer full, convenient access to inside of drum
- 12-gauge bolt ring closure, sponge rubber gasket and plated bolt/nut provide tight seal to help prevent leaks and spills
- Interior is coated with a corrosion inhibitor; choose optional phenolic/epoxy lining for added resistance
- 16-gauge steel lid and 18-gauge steel body and bottom meet strict wall thickness requirements to ensure strength, durability and long life

Item#	Description	Dimensions	Weight
DRM423-LD	Lined	ext. dia. 23.5" x 33" H	48 lbs.
DRM423-ULD	Unlined	ext. dia. 23.5" x 33" H	48 lbs.

Metric Equivalent:

Item#	Description	Dimensions	Weight
DRM423-LD	Lined	ext. dia. 59.7cm x 83.8cm H	21.8 kg
DRM423-ULD	Unlined	ext. dia. 59.7cm x 83.8cm H	21.8 kg

Specifications

Lining	Lined; Unlined
Thickness	1.2/1.2/1.2 mm
Color	Black/White
Dimensions	ext. dia. 23.5" x 33" H
Storage Capacity	55 gal.
Brand	Skolnik
Bung Type	No Bung Holes
Drum Type	Steel Drum
Interior Dimensions	22.5" Dia. x 32" H
Lid Type	Open-Head - Nut & Bolt Ring
Sold as	1 each
Weight	48 lbs.

# per Pallet	8
Composition	Drum - Carbon Steel Bung Gasket - EPDM Lining - Phenolic Epoxy
UNSPSC	24112108
Pigalog® Page Number	<u>Page 300</u>
Metric Equivalent	
Dimensions	ext. dia. 59.7cm x 83.8cm H
Storage Capacity	208.2 L
Weight	21.8 kg

Technical Information

Certifications, Approvals and Ratings

UN1A2/X435/S, UN1A2/Y1.5/150



One Pork Avenue • Tipton, PA 16684-0304
1-855-493-4647 • Fax: 1-800-621-7447 • newpig.com • hothogs@newpig.com