

## FTI .5 HP Electric Pump Motor



DRM432 Ideal For Acids; Corrosives; General-Purpose Chemicals,Max Flow Rate 20 gal./Minute,110V/50-60 Hz

Durable, splash-proof body is great for use with corrosives, acids and bleaches.

- High-output, variable-speed motor (3,500rpm to 10,000rpm) offers outstanding flow control
- Drip-proof design helps keep dispensing areas clean and dry
- System is continuous duty rated for extended operation
- Motor shuts automatically if it runs too long or too hot and restarts only with manual safety reset
- Excellent for use with corrosive-compatible pump tubes such as DRM435 or DRM508
- Pump tube not included

### Specifications

Brand	Finish Thompson
Compatible With	Acids; Corrosives; Chemicals
Explosion Proof	No
Horsepower	.5
Ideal For	Acids; Corrosives; General-Purpose Chemicals
Max Flow Rate	20 gal./Minute
Color	Gray
Max Viscosity	500 CentiPoise
Power Cord	12' w/ Plug
Powered By	Electric
Power Requirements	110V/50-60 Hz
Speed	Variable Speed
Use With Flammables	No
Sold as	1 each
Weight	8 lbs.
Composition	Steel
UNSPSC	40151529

### Metric Equivalent

Weight	3.6 kg
--------	--------

### Technical Information

## CountryShipOnly

This product can ONLY be shipped to: United States, Canada, Guam, Mexico, South Korea, Venezuela.

## Certifications, Approvals and Ratings

QPS Approved

## Technical Documents

[FTI Pumps](#)

[Pump Selection Guide](#)



**One Pork Avenue • Tipton, PA 16684-0304**

1-855-493-4647 • Fax: 1-800-621-7447 • [newpig.com](http://newpig.com) • [hothogs@newpig.com](mailto:hothogs@newpig.com)