

## FTI .5 HP Air-Operated Pump Motor

DRM433 Ideal For General-Purpose Chemicals,Max Flow Rate 22 gal./Minute,80-100 PSI @ 15-32 CFM

Versatile, air-powered pump completes a range of jobs.

- 1/2 hp, 300-6,000 RPM motor operates on 80 psi at 25 cfm
- Versatile pump is excellent for general light- to medium- viscosity jobs
- Use with a wide range of FTI Pump Tubes (available separately)
- Pumps up to 22 gpm
- Regulator valve and muffler provide quiet, adjustable performance
- Pump Tube not included



### Specifications

Air Line Input Fitting	.25" Air Line Fitting
Brand	Finish Thompson
Compatible With	Liquids up to 330 cps Viscosity
Explosion Proof	Yes
Horsepower	.5
Ideal For	General-Purpose Chemicals
Color	Blue/Silver
Max Flow Rate	22 gal./Minute
Max Viscosity	330 CentiPoise
Powered By	Air
Power Requirements	80-100 PSI @ 15-32 CFM
Speed	Single Speed
Use With Flammables	Yes
Sold as	1 each
Weight	4 lbs.
NSN (National Stock Number)	4930-01-392-8645
Composition	Cast Iron & Aluminum

## Metric Equivalent

Weight	1.8 kg
--------	--------

## Technical Information

### Technical Documents

[FTI Pumps](#)

[Pump Selection Guide](#)



# New Pig

World's best stuff for leaks, drips and spills.

**One Pork Avenue • Tipton, PA 16684-0304**

1-855-493-4647 • Fax: 1-800-621-7447 • [newpig.com](http://newpig.com) • [hothogs@newpig.com](mailto:hothogs@newpig.com)