

FTI .5 HP Air-Operated Pump Motor

DRM433 For Liquids up to 330 cps Viscosity, Max Flow Rate 22 gal./Minute, 80-100 PSI @ 15-32 CFM

Versatile, air-powered pump completes a range of jobs.

- 1/2 hp, 300-6,000 RPM motor operates on 80 psi at 25 cfm
- Versatile pump is excellent for general light- to medium- viscosity jobs
- Use with a wide range of FTI Pump Tubes (available separately)
- Pumps up to 22 gpm
- Regulator valve and muffler provide quiet, adjustable performance
- Pump Tube not included



Specifications

Air Line Input Fitting	.25" Air Line Fitting
Brand	Finish Thompson
Compatible With	Liquids up to 330 cps Viscosity
Explosion Proof	Yes
Horsepower	.5
Ideal For	General-Purpose Chemicals
Color	Blue/Silver
Max Flow Rate	22 gal./Minute
Max Viscosity	330 CentiPoise
Powered By	Air
Power Requirements	80-100 PSI @ 15-32 CFM
Speed	Single Speed
Use With Flammables	Yes
Sold as	1 each
Weight	4 lbs.
NSN (National Stock Number)	4930-01-392-8645
# per Pallet	180

Composition

Cast Iron & Aluminum

UNSPSC

40151529

Metric Equivalent

Weight

1.8 kg

Technical Information

Technical Documents

[FTI Pumps](#)

[Pump Selection Guide](#)



One Pork Avenue • Tipton, PA 16684-0304

1-855-493-4647 • Fax: 1-800-621-7447 • newpig.com • hothogs@newpig.com