

Retract-a-Clamp® Insulated Bonding/Grounding Wires

DRM442 1/4" Eyelet Grounding End, Hand Clamp Bonding End, 20' L

Wire creates safe grounding connection while staying coiled to avoid creating a tripping hazard.

- Bonding and grounding assembly controls static electricity to prevent sparking while transferring or storing flammable liquids; FM approved and NFPA 77 compliant
- Wire creates a solid grounding connection while staying coiled so as not to be a tripping hazard
- Vinyl coating protects wire from moisture and corrosion for longer life and to allow outdoor use



Specifications

Dimensions	20' L
Brand	Stewart R Browne
Bonding End	Hand Clamp
Grounding End	1/4" Eyelet
Insulated	Yes
Meets NFPA Standards	Yes
Sold as	1 each
Weight	1.5 lbs.
Composition	Clamp: Aluminum Wire: Vinyl-Coated Galvanized Steel
UNSPSC	39121613

Metric Equivalent

Weight	.7 kg
Dimensions	6.1m L

Technical Information

Certifications, Approvals and Ratings

FM Approved,NFPA 77

Technical Documents

29 CFR 1910.106(e)(6)(ii)



New Pig

World's best stuff for leaks, drips and spills.

One Pork Avenue • Tipton, PA 16684-0304

1-855-493-4647 • Fax: 1-800-621-7447 • newpig.com • hothogs@newpig.com