



Zee Line Steel Lever Action Drum Pump - Nitrile Seals

DRM461 Ideal For Fuel; Oils,Max Flow Rate 13 oz./Stroke,Max Viscosity 40 wt.

Economical drum pump features a durable all-steel body and is compatible with light oil (max 40 wt.), ATF, hydraulic fluid, kerosene and diesel fuel.

- Drum pump moves up to 13 oz. of fluid per stroke
- Compatible with light oils, transmission fluid and hydraulic fluid
- Fits 15- through 55-gallon drums with 2" NPT bungs
- Maximum recommended viscosity equals SAE 30-40 weight
- Not for use with water
- Includes three handle pin locations which each provide different flow rates per stroke: 8 oz. (closest to piston rod), 10 oz. (middle) or 13 oz. (farthest from piston rod)

Specifications

| | |
|------------------------------------|---------------------------------------------------------------------|
| Use With | 15 to 55 gal. Drum w/ 2" NPT Bung |
| Brand | Zeeline |
| Compatible With | Light Oil (Max 40 wt.); ATF; Hydraulic Fluid; Kerosene; Diesel Fuel |
| Ideal For | Fuel; Oils |
| Manual Pump Type | Lever Operated |
| Max Flow Rate | 13 oz./Stroke |
| Color | Silver |
| Max Viscosity | 40 wt. |
| Powered By | Manual |
| Use With Flammables | No |
| Sold as | 1 each |
| Weight | 6 lbs. |
| NSN (National Stock Number) | 4930-01-443-9635 |

Composition

Body: Steel
Rings: Brass
Pistons: Zinc
Tube: PVC

Seals: Buna N

UNSPSC

40151529

Pigalog® Page Number

Page 331

Metric Equivalent

Weight

2.7 kg

Technical Information

Technical Documents

Pump Selection Guide



New Pig

World's best stuff for leaks, drips and spills.

One Pork Avenue • Tipton, PA 16684-0304

1-855-493-4647 • Fax: 1-800-621-7447 • newpig.com • hothogs@newpig.com