



## Zee Line Steel Lever Action Drum Pump - Nitrile Seals

DRM461 For Light Oil (Max 40 wt.); ATF; Hydraulic Fluid; Kerosene; Diesel Fuel, Max Flow Rate 13 oz./Stroke, Max Viscosity 40 wt.

Economical drum pump features a durable all-steel body and is compatible with light oil (max 40 wt.), ATF, hydraulic fluid, kerosene and diesel fuel.

- Drum pump moves up to 13 oz. of fluid per stroke
- Compatible with light oils, transmission fluid and hydraulic fluid
- Fits 15- through 55-gallon drums with 2" NPT bungs
- Maximum recommended viscosity equals SAE 30-40 weight
- Not for use with water
- Includes three handle pin locations which each provide different flow rates per stroke: 8 oz. (closest to piston rod), 10 oz. (middle) or 13 oz. (farthest from piston rod)

### Specifications

<b>Use With</b>	15 to 55 gal. Drum w/ 2" NPT Bung
<b>Brand</b>	Zeeline
<b>Compatible With</b>	Light Oil (Max 40 wt.); ATF; Hydraulic Fluid; Kerosene; Diesel Fuel
<b>Ideal For</b>	Fuel; Oils
<b>Manual Pump Type</b>	Lever Operated
<b>Max Flow Rate</b>	13 oz./Stroke
<b>Color</b>	Silver
<b>Max Viscosity</b>	40 wt.
<b>Powered By</b>	Manual
<b>Use With Flammables</b>	No
<b>Distributor Part Number</b>	4284390;04088x40205
<b>Sold as</b>	1 each
<b>Weight</b>	6 lbs.
<b>NSN (National Stock Number)</b>	4930-01-443-9635
<b># per Pallet</b>	100

## Composition

Body - Steel  
Rings - Brass  
Pistons - Zinc  
Tube - PVC  
Seals - Buna N

## UNSPSC

40151529

## Pigalog® Page Number

Page 319

## Metric Equivalent

## Weight

2.7 kg

## Technical Information

## Technical Documents

## Pump Selection Guide



**New Pig**

World's best stuff for leaks, drips and spills.

**One Pork Avenue • Tipton, PA 16684-0304**

1-855-493-4647 • Fax: 1-800-621-7447 • [newpig.com](http://newpig.com) • [hothogs@newpig.com](mailto:hothogs@newpig.com)