

FTI PFS Pick-Up Tube

DRM508 40" L, For Mild Corrosives; Non-Flammable Solvents

Stainless-steel construction is excellent for general-purpose pumping of solvents and mild corrosives.

- Stainless Steel Pump Tube handles solvents, mild corrosives and organic acids of light to medium viscosity
- Seal-less Tube is 40" long
- Handles temperatures up to 220° F
- 30-minute run-dry capability prevents damage
- Double-suction impeller improves pump performance
- We recommend pairing with FTI .5 Horsepower Drum Pump Motor (DRM432) or FTI Air Drum Pump Motor (DRM433); pump motor sold separately
- Discharge Hose sold separately



Specifications

Dimensions	40" L
Brand	Finish Thompson
Compatible With	Mild Corrosives; Non-Flammable Solvents
Ideal For	Corrosives; Solvents
Temperature Limit	Maximum Temperature 220°F (104°C)
Use With Flammables	No
Color	Silver
Sold as	1 each
Weight	11.3 lbs.
# per Pallet	72
Composition	Outer Material, Shaft Material: 316 Stainless Steel Internals: ETFE, PTFE, Stainless Steel, FKM
UNSPSC	40151529

Metric Equivalent

Weight	5.1 kg
Dimensions	102cm L

Technical Information

Technical Documents

PFS_FTIPumpsChemGuide



One Pork Avenue • Tipton, PA 16684-0304

1-855-493-4647 • Fax: 1-800-621-7447 • newpig.com • hothogs@newpig.com