

Tuffite® Uninsulated Bonding/Grounding Wires

DRM627 Hand Clamp Grounding End, Hand Clamp Bonding End, 3'



Provides NFPA- and FM-compliant grounding for storage and transfer of flammables.

- Bonding and grounding assembly controls static electricity to prevent sparking while transferring or storing flammable liquids; FM approved and NFPA 77 compliant
- 3' uncoated galvanized steel wire is easy to inspect for dangerous breaks and frays
- Available with multiple clamp options to suit your use and ensure a safe, solid connection



Specifications

Dimensions	3' L
Brand	Stewart R Browne
Insulated	No
Meets NFPA Standards	Yes
Sold as	1 each
Weight	1 lb.
Composition	Clamp - Aluminum Wire - Galvanized Steel
Bonding End	Hand Clamp
Grounding End	Hand Clamp
UNSPSC	39121613
Pigalog® Page Number	Page 340

Metric Equivalent

Dimensions	91.4cm L
Weight	.5 kg

Technical Information

Certifications, Approvals and Ratings

FM Approved, NFPA 77

Technical Documents

29 CFR 1910.106(e)(6)(ii)



New Pig

World's best stuff for leaks, drips and spills.

One Pork Avenue • Tipton, PA 16684-0304

1-855-493-4647 • Fax: 1-800-621-7447 • newpig.com • hothogs@newpig.com