

Tuffite® Uninsulated Bonding/Grounding Wires

DRM627 Hand Clamp Grounding End,Hand Clamp Bonding End,3' L



- Provides NFPA- and FM-compliant grounding for storage and transfer of flammables.
- Bonding and grounding assembly controls static electricity to prevent sparking while transferring or storing flammable liquids; FM approved and NFPA 77 compliant
 - 3' uncoated galvanized steel wire is easy to inspect for dangerous breaks and frays
 - Available with multiple clamp options to suit your use and ensure a safe, solid connection



Specifications

Dimensions	3' L
Brand	Stewart R Browne
Bonding End	Hand Clamp
Grounding End	Hand Clamp
Insulated	No
Meets NFPA Standards	Yes
Sold as	1 each
Weight	1 lb.
Composition	Clamp: Aluminum Wire: Galvanized Steel
UNSPSC	39121613
Pigalog® Page Number	Page 341

Metric Equivalent

Weight	.5 kg
Dimensions	91cm L

Technical Information

Certifications, Approvals and Ratings

FM Approved,NFPA 77

Technical Documents

29 CFR 1910.106(e)(6)(ii)



New Pig

World's best stuff for leaks, drips and spills.

One Pork Avenue • Tipton, PA 16684-0304

1-855-493-4647 • Fax: 1-800-621-7447 • newpig.com • hothogs@newpig.com