

5-Gallon Open-Head UN Rated Steel Drum

DRM682 Storage Capacity 5 gal., UN1A2/X60/S, UN1A2/Y1.8/150,0.9/0.9/0.9 mm

Tough, UN Rated open top drums are made for hazardous materials, so you can rely on them to deliver safety and compliance.



- UN Rated and tested to help ensure safe shipping of hazardous materials
- Open-head design and removable lid offer full, convenient access to inside of drum
- 12-gauge bolt ring closure, sponge rubber gasket and plated bolt/nut provide tight seal to help prevent leaks and spills
- Interior is coated with a corrosion inhibitor; choose optional phenolic/epoxy lining for added resistance
- 20-gauge steel lid, body and bottom meet strict wall thickness requirements to ensure strength, durability and long life

Item#	Description	Dimensions	Weight
DRM682-LD	Lined	ext. dia. 15" x 11" H	10 lbs.
DRM682-ULD	Unlined	ext. dia. 15" x 11" H	10 lbs.

Metric Equivalent:

Item#	Description	Dimensions	Weight
DRM682-LD	Lined	ext. dia. 38.1cm x 27.9cm H	4.5 kg
DRM682-ULD	Unlined	ext. dia. 38.1cm x 27.9cm H	4.5 kg

Specifications

Dimensions	ext. dia. 15" x 11" H
Storage Capacity	5 gal.
Brand	Skolnik
Bung Type	No Bung Holes
Drum Type	New Steel Drum
Lid Type	Open-Head - Nut & Bolt Ring
Color	Black/White
Lining	Lined; Unlined
Thickness	0.9/0.9/0.9 mm
Distributor Part Number	5897780;04088x30084
Sold as	1 each
Weight	10 lbs.

# per Pallet	54
--------------	----

Composition

Drum - Steel
Bolt Ring - 13-Gauge Steel
Lining - Phenolic Epoxy
Gasket - EPDM

UNSPSC	24112108
--------	----------

Pigalog® Page Number	<u>Page 300</u>
----------------------	-----------------

Metric Equivalent

Dimensions	ext. dia. 38.1cm x 27.9cm H
------------	-----------------------------

Storage Capacity	18.9 L
------------------	--------

Weight	4.5 kg
--------	--------

Technical Information

Certifications, Approvals and Ratings

UN1A2/X60/S,UN1A2/Y1.8/150



One Pork Avenue • Tipton, PA 16684-0304

1-855-493-4647 • Fax: 1-800-621-7447 • newpig.com • hothogs@newpig.com