

# 10-Gallon Open-Head UN Rated Steel Drum

DRM685 Storage Capacity 10 gal., UN1A2/X120/S, UN1A2/Y1.8/150, Thickness 0.9/0.9/0.9 mm

Tough, UN Rated open top drums are made for hazardous materials, so you can rely on them to deliver safety and compliance.

- UN Rated and tested to help ensure safe shipping of hazardous materials
- Open-head design and removable lid offer full, convenient access to inside of drum
- 12-gauge bolt ring closure, sponge rubber gasket and plated bolt/nut provide tight seal to help prevent leaks and spills
- Interior is coated with a corrosion inhibitor; choose optional phenolic/epoxy lining for added resistance
- 20-gauge steel lid, body and bottom meet strict wall thickness requirements to ensure strength, durability and long life



Item#	Description	Dimensions	Weight
DRM685-LD	Lined	ext. dia. 14.25" x 19" H	15 lbs.
DRM685-ULD	Unlined	ext. dia. 14.25" x 19" H	15 lbs.

## Metric Equivalent:

Item#	Description	Dimensions	Weight
DRM685-LD	Lined	ext. dia. 36cm x 48cm H	6.8 kg
DRM685-ULD	Unlined	ext. dia. 36cm x 48cm H	6.8 kg

## Specifications

Dimensions	ext. dia. 14.25" x 19" H
Storage Capacity	10 gal.
Brand	Skolnik
Bung Type	No Bung Holes
Drum Type	New Steel Drum
Interior Dimensions	13.25" Dia. x 18" H
Color	Black/White
Lid Type	Open-Head - Nut & Bolt Ring
Lining	Lined; Unlined
Thickness	0.9/0.9/0.9 mm
Sold as	1 each
Weight	15 lbs.

# per Pallet	36
Composition	Drum - Steel Gasket - EPDM
UNSPSC	24112108
Pigalog® Page Number	<u>Page 290</u>

## Metric Equivalent

Dimensions	ext. dia. 36cm x 48cm H
Storage Capacity	37.9 L
Weight	6.8 kg

## Technical Information

### Certifications, Approvals and Ratings

UN1A2/X120/S,UN1A2/Y1.8/150



**One Pork Avenue • Tipton, PA 16684-0304**

1-855-493-4647 • Fax: 1-800-621-7447 • [newpig.com](http://newpig.com) • [hothogs@newpig.com](mailto:hothogs@newpig.com)