

Zee Line Steel Lever Action Pail Pump - Nitrile Seals

DRM694 For Oil-Based Liquids; ATF; Gear Lube (Max 140 wt.),Max Flow Rate 2.3 oz./Stroke,Max Viscosity 140 wt.

Just clip this cover to the top of your pail and you've created a mobile dispensing station for oil-based liquids, ATF and gear lube (max 140 wt.).

- Turns any pail up to 6.5 gallons into a mini dispensing station
- Dispenses up to 3 oz. per stroke of motor oil, hydraulic oil, automatic transmission fluid or gear lubricants up to 140 weight
- Nitrile O-ring and brass-ringed piston are designed for use with petroleum-based oils and lubricants
- Includes 4' clear vinyl hose with a curved discharge nozzle



Specifications

| | |
|-------------------------|-------------------------------------------------|
| Use With | 5 to 6.5 gal. Open-Head Pail |
| Brand | Zeeline |
| Compatible With | Oil-Based Liquids; ATF; Gear Lube (Max 140 wt.) |
| Ideal For | Oils |
| Manual Pump Type | Lever Operated |
| Max Flow Rate | 2.3 oz./Stroke |
| Color | Red |
| Max Viscosity | 140 wt. |
| Powered By | Manual |
| Use With Flammables | No |
| Distributor Part Number | 2938519;04088x30024 |
| Sold as | 1 each |
| Weight | 8 lbs. |
| # per Pallet | 240 |

Composition

Pail Cover - Steel
Pump Housing - Steel, Polypropylene
Diaphragm - Viton
Seals - Nitrile
Hoses, Wand - PVC

UNSPSC

40151529

Pigalog® Page NumberPage 319**Metric Equivalent****Weight**

3.6 kg

Technical Information**Technical Documents****Pump Selection Guide****New Pig**

World's best stuff for leaks, drips and spills.

One Pork Avenue • Tipton, PA 16684-0304

1-855-493-4647 • Fax: 1-800-621-7447 • newpig.com • hothogs@newpig.com