

FTI .67 HP Electric Explosion-Proof Drum Pump System With TTS Pick-Up Tube

DRM8000 For Corrosives; Solvents; Flammables, Max Flow Rate 10 gal./Minute, For 55 gal. Drum w/ 2" NPT Bung

Transfer flammable or corrosive liquids from a 55-gallon steel drum with this explosion-proof, electric drum pump system with stainless steel pick-up tube.

- Explosion-proof pump motor is double insulated for extra protection from heat; overload feature shuts motor automatically when it runs too hot
- Digital display provides easy monitoring of pump activity
- Included 40"-long TTS stainless steel pick-up tube safely dispenses corrosives, solvents, flammable or combustible liquids from 55-gallon drums
- Included static hose protection kit grounds motor to eliminate static-generated sparks when pumping flammables
- Included IPS Adapter threads into bung opening to hold pump tube upright
- NOTE: Power cord is included, but plug must be installed by customer to match specific receptacle being used



Specifications

Speed	Variable Speed
Max Flow Rate	10 gal./Minute
Max Viscosity	500 CentiPoise
Use With	55 gal. Drum w/ 2" NPT Bung
Color	Black/Blue/Silver
Brand	Finish Thompson FTI
Bung Opening	2" NPT Bung
Compatible With	Corrosives; Solvents; Flammables
Explosion Proof	Yes
Horsepower	.67
Ideal For	Corrosives; Flammables; Solvents
Power Cord	12' w/o Plug
Powered By	Electric
Temperature Limit	Maximum Temperature 150°F (66°C)
Use With Flammables	Yes

Sold as	1 each
Weight	32.39 lbs.
Composition	<p>Motor: Steel & Plastic</p> <p>Pick-Up Tube: Stainless Steel</p> <p>Hose: Wire Reinforced Polyethylene</p> <p>Clamps - Aluminum & Stainless Steel</p> <p>Hose Clamps, Wire - Stainless Steel</p> <p>Drum Adapter: Stainless Steel</p>
Includes	<p>1 - FTI .67 HP Electric Explosion-Proof Pump Motor (DRM1269)</p> <p>1 - 40" L FTI TTS Pick-Up Tube (DRM271)</p> <p>1 - int. dia. 1" x 4' L FTI Static Hose Protection Kit (DRM272)</p> <p>1 - FTI IPS Adapter (DRM514)</p>
Power Requirements	115V/60 Hz
UNSPSC	40151529
Pigalog® Page Number	Page 325

Metric Equivalent

Weight	14.7 kg
---------------	---------

Technical Information

Certifications, Approvals and Ratings

QPS Approved

USOnly

This product can ONLY be shipped to the United States.

Certifications, Approvals and Ratings

QPS Approved

USOnly

This product can ONLY be shipped to the United States.

Technical Documents

[TTS_FTIPumpsChemGuide](#)

[Pump Selection Guide](#)



One Pork Avenue • Tipton, PA 16684-0304

1-855-493-4647 • Fax: 1-800-621-7447 • newpig.com • hothogs@newpig.com

