

FTI .5 HP Air-Operated Drum Pump System with PFS Pick-Up Tube

DRM8006 Ideal For Corrosives; Solvents,Max Flow Rate 22 gal./Minute,For 55 gal. Drum w/ 2" NPT Bung

Dispense mild corrosives and non-flammable liquids from 55-gallon drums with this air-powered drum pump system with steel pick-up tube.

- .5 hp, 300-6,000 RPM motor operates on 80 psi at 25 cfm and pumps up to 22 gpm; excellent for general light- to medium- viscosity jobs
- Includes 40"- long stainless-steel pump tube that fits a 55-gallon drum; handles temperatures up to 220° F
- Includes 5'- long reinforced PVC discharge hose with clamp
- Included stainless steel adaptor threads into 2" bung opening to hold pump tube upright and secure
- Included filter/lubricator helps ensure the long-term performance of your air pump motor



Specifications

Use With	55 gal. Drum w/ 2" NPT Bung
Air Line Input Fitting	.25" Air Line Fitting
Brand	Finish Thompson
Bung Opening	2" NPT Bung
Compatible With	Mild Corrosives; Non-Flammable Solvents
Explosion Proof	No
Color	Blue/Silver
Horsepower	.5
Ideal For	Corrosives; Solvents
Max Flow Rate	22 gal./Minute
Max Viscosity	330 CentiPoise
Powered By	Air
Power Requirements	80-100 PSI @ 15-32 CFM
Speed	Single Speed
Temperature Limit	Maximum Temperature 220°F (104°C)
Use With Flammables	No
Sold as	1 each
Weight	19.47 lbs.

Composition

Motor: Cast Iron, Aluminum

Pick-Up Tube Outer Shaft Material: 316 Stainless Steel

Internals: ETFE, PTFE, Stainless Steel, FKM

Hose: Reinforced PVC

Drum Adapter: Stainless Steel

Filter, Lubricator: Steel

Includes

1 - FTI .5 HP Air-Operated Pump Motor (DRM433)

1 - 40" L FTI PFS Pick-Up Tube (DRM508)

1 - int. dia. 1" x 5' L PVC Discharge Hose (DRM888)

1 - FTI IPS Adapter (DRM513)

1 - FTI Filter/Lubricator (DRM434)

UNSPSC

40151529

Pigalog® Page Number

Page 338

Metric Equivalent

Weight

8.8 kg

Technical Information

Technical Documents

[PFS_FTIPumpsChemGuide](#)

[Pump Selection Guide](#)



One Pork Avenue • Tipton, PA 16684-0304

1-855-493-4647 • Fax: 1-800-621-7447 • newpig.com • hothogs@newpig.com