

FTI .5 HP Air-Operated Drum Pump System with PFS Pick-Up Tube

DRM8006 For Mild Corrosives; Non-Flammable Solvents, Max Flow Rate 22 gal./Minute, For 55 gal. Drum w/ 2" NPT Bung

Dispense mild corrosives and non-flammable liquids from 55-gallon drums with this air-powered drum pump system with steel pick-up tube.

- .5 hp, 300-6,000 RPM motor operates on 80 psi at 25 cfm and pumps up to 22 gpm; excellent for general light- to medium- viscosity jobs
- Includes 40"- long stainless-steel pump tube that fits a 55-gallon drum; handles temperatures up to 220° F
- Includes 5'- long reinforced PVC discharge hose with clamp
- Included stainless steel adaptor threads into 2" bung opening to hold pump tube upright and secure
- Included filter/lubricator helps ensure the long-term performance of your air pump motor



Specifications

| | |
|------------------------|---|
| Use With | 55 gal. Drum w/ 2" NPT Bung |
| Air Line Input Fitting | .25" Air Line Fitting |
| Brand | Finish Thompson |
| Bung Opening | 2" NPT Bung |
| Compatible With | Mild Corrosives; Non-Flammable Solvents |
| Explosion Proof | No |
| Color | Blue/Silver |
| Horsepower | .5 |
| Ideal For | Corrosives; Solvents |
| Max Flow Rate | 22 gal./Minute |
| Max Viscosity | 330 CentiPoise |
| Powered By | Air |
| Power Requirements | 80-100 PSI @ 15-32 CFM |
| Speed | Single Speed |
| Temperature Limit | Maximum Temperature 220°F (104°C) |
| Use With Flammables | No |
| Sold as | 1 each |
| Weight | 19.47 lbs. |

Composition

Motor: Cast Iron, Aluminum

Pick-Up Tube Outer Shaft Material: 316 Stainless Steel

Internals: ETFE, PTFE, Stainless Steel, FKM

Hose: Reinforced PVC

Drum Adapter: Stainless Steel

Filter/Lubricator: Steel

Includes

1 - FTI .5 HP Air-Operated Pump Motor (DRM433)

1 - 40" L FTI PFS Pick-Up Tube (DRM508)

1 - int. dia. 1" x 5' L PVC Discharge Hose (DRM888)

1 - FTI IPS Adapter (DRM513)

1 - FTI Filter/Lubricator (DRM434)

UNSPSC

40151529

Pigalog® Page Number

Page 326

Metric Equivalent

Weight

8.8 kg

Technical Information

USOnly

This product can ONLY be shipped to the United States.

Technical Documents

[PFS_FTIPumpsChemGuide](#)

[Pump Selection Guide](#)



One Pork Avenue • Tipton, PA 16684-0304

1-855-493-4647 • Fax: 1-800-621-7447 • newpig.com • hothogs@newpig.com