



FTI .5 HP Electric Drum Pump System with PFP Pick-Up Tube

DRM8007 For Acids; Bases; Other Corrosives, Max Flow Rate 20 gal./Minute, For 55 gal. Drum w/ 2" NPT Bung

Dispense mild corrosives and non-flammable liquids from 55-gallon drums with this high flow rate electric drum pump system with poly pick-up tube.

- High-output, variable-speed motor (3,500rpm to 10,000rpm) offers outstanding flow control in a drip-proof design
- Pump motor is continuous duty rated for extended operation; motor shuts off if it runs too long or too hot and restarts only with manual safety reset
- Includes 40"-long polypropylene sealless pick-up tube to fit 55-gallon drums
- Includes 5'- long reinforced PVC discharge hose with clamp
- Included IPS Adapter threads into bung opening to hold pump tube upright



Specifications

| | |
|----------------------------|--|
| Speed | Variable Speed |
| Max Flow Rate | 20 gal./Minute |
| Max Viscosity | 500 CentiPoise |
| Use With | 55 gal. Drum w/ 2" NPT Bung |
| Color | Black/Blue/Gray |
| Brand | Finish Thompson FTI |
| Bung Opening | 2" NPT Bung |
| Compatible With | Acids; Bases; Other Corrosives |
| Explosion Proof | No |
| Horsepower | .5 |
| Ideal For | Acids; Bases; Corrosives |
| Power Cord | 12' w/ Plug |
| Powered By | Electric |
| Temperature Limit | Maximum Temperature 160°F (71°C) |
| Use With Flammables | No |
| Sold as | 1 each |
| Weight | 15.34 lbs. |
| Composition | Motor: Steel & Plastic Pick-Up Tube: Outer Material - Polypropylene |

Shaft Material - Alloy 625
Internals - Polypropylene, PTFE, PVDF, FKM
Hose: Reinforced PVC
Drum Adapter: Polypropylene

Includes

1 - FTI .5 HP Electric Pump Motor (DRM432)
1 - 40" L FTI PFP Pick-Up Tube (DRM435)
1 - int. dia. 1" x 5' L PVC Discharge Hose (DRM888)
1 - FTI IPS Adapter (DRM512)

Power Requirements

110V/50-60 Hz

UNSPSC

40151529

Pigalog® Page Number

Page 325

Metric Equivalent

Weight

7 kg

Technical Information

Certifications, Approvals and Ratings

QPS Approved

USOnly

This product can ONLY be shipped to the United States.

Certifications, Approvals and Ratings

QPS Approved

USOnly

This product can ONLY be shipped to the United States.

Technical Documents

[PFP_FTIPumpsChemGuide](#)

[Pump Selection Guide](#)



One Pork Avenue • Tipton, PA 16684-0304

1-855-493-4647 • Fax: 1-800-621-7447 • newpig.com • hothogs@newpig.com