

FTI Lithium Battery-Operated Drum Pump System with EFS Pick-Up Tube

DRM8009 For Light Acids; Solvents; Sodium Hypochlorite; Cleaners; Coolants; DEF, Max Flow Rate 14 gal./Minute, For 55 gal. Drum w/ 2" NPT Bung

Battery-powered drum pump system with steel pick-up tube for use with light acids, solvents, sodium hypochlorite, cleaners, coolants and DEF in 55-gallon drums in non-explosive areas.

- Light-weight, portable drum pump motor can be used in different locations, unlike standard pumps that require power cords or air lines
- Pump motor maximum flow rate is 14 gal./minute; pumps up to 450 gallons per charge
- Powered by built-in 12V rechargeable lithium battery (charging kit also included)
- Included 40"- long stainless steel pick-up tube fits 55-gallon drums
- Includes a flexible 5'- long PVC discharge hose
- Includes stainless steel IPS adaptor that threads into 2" bung opening to hold tote upright and secure; allows you to keep both hands free for dispensing



Specifications

Speed	Dual Speed
Max Flow Rate	14 gal./Minute
Max Viscosity	100 CentiPoise
Use With	55 gal. Drum w/ 2" NPT Bung
Color	Gray/Silver
Brand	Finish Thompson FTI
Bung Opening	2" NPT Bung
Compatible With	Light Acids; Solvents; Sodium Hypochlorite; Cleaners; Coolants; DEF
Explosion Proof	No
Ideal For	Acids; Coolants; Corrosives; General-Purpose Chemicals; Solvents
Power Cord	115V Charger Kit
Powered By	Battery
Temperature Limit	Maximum Temperature 212°F (100°C)
Use With Flammables	No

Sold as	1 each
Weight	11.94 lbs.
Composition	Motor: Steel & Plastic Pick-Up Tube: Tube - 316 stainless steel Shaft - 316 stainless steel O-ring - FKM Impeller - ETFE Hose: Reinforced PVC Drum Adapter: Stainless Steel
Includes	1 - FTI Lithium Battery-Operated Pump Motor (DRM1423) 1 - 40" L FTI EFS Pick-Up Tube (DRM1424) 1 - int. dia. 0.75" x 5' L PVC Discharge Hose (DRM8011) 1 - FTI IPS Adapter (DRM8012)
Power Requirements	12V 3200mAh Lithium Ion Battery
UNSPSC	40151529
Pigalog® Page Number	Page 326

Metric Equivalent

Weight	5.4 kg
---------------	--------

Technical Information

USOnly

This product can ONLY be shipped to the United States.

StateNoShip

This product is subject to restrictions and cannot be shipped to Alaska or Hawaii.

Technical Documents

[EFS_FTIPumpsChemGuide](#)

[Pump Selection Guide](#)



One Pork Avenue • Tipton, PA 16684-0304

1-855-493-4647 • Fax: 1-800-621-7447 • newpig.com • hothogs@newpig.com