

FTI .5 HP Air-Operated TM Drum Mixer System

DRM8101 Ideal For Corrosives; Flammables; Solvents, For 55 gal. Drum w/ 2" NPT Bung

Mix dyes, inks, paints, solvents, mild corrosives and flammables from 55-gallon steel or poly drums with this air-powered drum mixing system.

- .5 hp, 300-6,000 RPM motor operates on 80 psi at 25 cfm and pumps up to 22 gpm; excellent for general light- to medium- viscosity jobs
- Regulator valve and muffler provide quiet, adjustable performance
- Included 40" 4-blade drum mixer fits 55-gallon drums with a 2" NPT bungs and mixes top-to-bottom for rapid suspension of settled solids
- Includes stainless steel IPS adaptor that threads into 2" bung opening to hold mixer upright and secure; allows you to keep both hands free for mixing
- Included filter/lubricator helps ensure the long-term performance of your air pump motor



Specifications

Use With	55 gal. Drum w/ 2" NPT Bung
Air Line Input Fitting	.25" Air Line Fitting
Brand	Finish Thompson
Bung Opening	2" NPT Bung
Compatible With	Dyes; Inks; Paints; Solvents; Mild Corrosives; Flammables
Explosion Proof	No
Color	Blue/Silver
Horsepower	.5
Ideal For	Corrosives; Flammables; Solvents
Max Viscosity	330 CentiPoise
Power Cord	12' w/ Plug
Powered By	Air
Power Requirements	80-100 PSI @ 15-32 CFM
Speed	Single Speed
Temperature Limit	200°F (93°C) Maximum Temperature
Use With Flammables	Yes
Sold as	1 each
Weight	15.95 lbs.

Composition

Motor: Cast Iron, Aluminum
Mixer Tube: 316 Stainless Steel
Shaft: 316 Stainless Steel
Center Bearing: PTFE
Drum Adapter: Stainless Steel

Includes

1 - FTI .5 HP Air-Operated Pump Motor (DRM433)
1 - 40" L FTI TM Drum Mixer (DRM1425)
1 - FTI IPS Adapter (DRM8013)
1 - FTI Filter/Lubricator (DRM434)

UNSPSC

23191101

Pigalog® Page Number

Page 339

Metric Equivalent**Weight**

7.2 kg

Technical Information**USOnly**

This product can ONLY be shipped to the United States.



One Pork Avenue • Tipton, PA 16684-0304

1-855-493-4647 • Fax: 1-800-621-7447 • newpig.com • hothogs@newpig.com