



## 55-Gallon Quick-Style Open-Head UN Rated Steel Drum

DRM837 Storage Capacity 55 gal.,UN1A2/X430/S,Thickness 1.5/1.5/1.5 mm

Tough, UN Rated open top drums are made for hazardous materials, so you can rely on them to deliver safety and compliance.

- UN Rated and tested to help ensure safe shipping of hazardous materials
- Quick-style lever lock rings make it easy to comply with closure regs; no tools required
- Open-head design and removable lid offer full, convenient access to inside of drum
- Shippable "as is" so there's no need to switch closure rings as with other leverlock ring assemblies
- Interior is coated with a corrosion inhibitor; choose optional phenolic/epoxy lining for added resistance
- 16-gauge steel lid, body and bottom meet strict wall thickness requirements to ensure strength, durability and long life

Item#	Description	Dimensions	Weight
DRM837-LD	Lined	ext. dia. 23.5" x 33" H	60 lbs.
DRM837-ULD	Unlined	ext. dia. 23.5" x 33" H	60 lbs.

### Metric Equivalent:

Item#	Description	Dimensions	Weight
DRM837-LD	Lined	ext. dia. 60cm x 84cm H	27.2 kg
DRM837-ULD	Unlined	ext. dia. 60cm x 84cm H	27.2 kg

### Specifications

Dimensions	ext. dia. 23.5" x 33" H
Storage Capacity	55 gal.
Brand	Skolnik
Bung Type	No Bung Holes
Drum Type	New Steel Drum
Lid Type	Open-Head - Quick-Style Lever Lock Band
Color	Black/White
Lining	Lined; Unlined
Thickness	1.5/1.5/1.5 mm
Sold as	1 each

Weight	60 lbs.
# per Pallet	8
Composition	Drum: 16-Gauge Steel Lever Ring: Galvanized Steel Lining: Phenolic Epoxy Gasket: EPDM
UNSPSC	24112108
Pigalog® Page Number	<u>Page 306</u>

Metric Equivalent

Storage Capacity	208.2 L
Weight	27.2 kg
Dimensions	ext. dia. 60cm x 84cm H

Technical Information

Certifications, Approvals and Ratings

UN1A2/X430/S



**One Pork Avenue • Tipton, PA 16684-0304**  
1-855-493-4647 • Fax: 1-800-621-7447 • [newpig.com](http://newpig.com) • [hothogs@newpig.com](mailto:hothogs@newpig.com)