

Quick-Style Open-Head UN Rated Steel Salvage Drum

DRM842 Storage Capacity 55 gal.,UN1A2/X400/S,Thickness 1.5/1.2/1.2 mm

Ship damaged or leaking containers of hazardous materials in these UN Rated open top steel salvage drums.

- UN Rated and tested to help ensure safe shipping of hazardous materials
- Quick-style lever lock rings make it easy to comply with closure regs; no tools required
- Open-head design and removable lid offer full, convenient access
- Shippable "as is" so there's no need to switch closure rings
- High-visibility yellow with red multi-lingual
 "Salvage Drum" markings clearly identify drum
- Interior is coated with a corrosion inhibitor; choose optional phenolic/epoxy lining for added resistance
- 16-gauge steel lid, body and bottom meet strict wall thickness requirements to ensure strength, durability and long life

Item#	Description	Dimensions	Weight
DRM842-LD	Lined	ext. dia. 23.06" x 34.75" H	50 lbs.
DRM842-ULD	Unlined	ext. dia. 23.06" x 34.75" H	50 lbs.

Metric Equivalent:

Item#	Description	Dimensions	Weight
DRM842-LD	Lined	ext. dia. 59cm x 88cm H	22.7 kg
DRM842-ULD	Unlined	ext. dia. 59cm x 88cm H	22.7 kg

Specifications

Lining

Dimensions	ext. dia. 23.06" x 34.75" H
Storage Capacity	55 gal.
Brand	Skolnik
Bung Type	No Bung Holes
Drum Type	New Steel Drum
Interior Dimensions	22.5" Dia. x 33" H
Color	Red/Yellow
Lid Type	Open-Head - Quick-Style Lever Lock Band

Lined; Unlined

Thickness	1.5/1.2/1.2 mm
Sold as	1 each
Weight	50 lbs.
# per Pallet	8
Composition	Drum: 16-Gauge Steel Ring: Galvanized Steel Lining: Rust Inhibitor (Unlined), Phenolic, Epoxy (Lined) Gasket: EPDM
UNSPSC	24112108
Pigalog® Page Number	Page 311
Metric Equivalent	

Storage Capacity	208.2 L
Weight	22.7 kg
Dimensions	ext. dia. 59cm x 88cm H

Technical Information

Certifications, Approvals and Ratings

UN1A2/X400/S

Technical Documents

49 CFR 173.3(c)(1)



One Pork Avenue • Tipton, PA 16684-0304

1-855-493-4647 • Fax: 1-800-621-7447 • newpig.com • hothogs@newpig.com