

30-Gallon Tight-Head UN Rated Steel Drum



DRM845 Storage Capacity 30 gal., UN1A1/Y1.5/300, Thickness 0.9/0.9/0.9 mm

Tough, UN Rated drums are made for hazardous materials, so you can rely on them to deliver safety and compliance.

- UN Rated and tested to help ensure safe shipping of hazardous materials
- Tight-head design is equipped with 2" NPT and 3/4" NPT bungs
- Interior is coated with a corrosion inhibitor; choose optional phenolic/epoxy lining for added resistance
- 20-gauge steel top, body and bottom meet strict wall thickness requirements to ensure strength, durability and long life

Item#	Description	Dimensions	Weight
DRM845-LD	Lined	ext. dia. 19.25" x 29.5" H	26 lbs.
DRM845-ULD	Unlined	ext. dia. 19.25" x 29.5" H	26 lbs.

Metric Equivalent:

Item#	Description	Dimensions	Weight
DRM845-LD	Lined	ext. dia. 49cm x 75cm H	11.8 kg
DRM845-ULD	Unlined	ext. dia. 49cm x 75cm H	11.8 kg

Specifications

Dimensions	ext. dia. 19.25" x 29.5" H
Storage Capacity	30 gal.
Brand	Skolnik
Bung Type	2" NPT and .75" NPT (Tri-Sure) Bungs
Drum Type	New Steel Drum
Interior Dimensions	18.75" Dia. x 29" H
Color	Black/White
Lid Type	Tight-Head
Lining	Lined; Unlined
Thickness	0.9/0.9/0.9 mm
Sold as	1 each
Weight	26 lbs.
# per Pallet	15
Composition	Drum: Steel

Bung Gasket: Buna-N

UNSPSC

24112108

Pigalog® Page Number

Page 307

Metric Equivalent

Storage Capacity

113.6 L

Weight

11.8 kg

Dimensions

ext. dia. 49cm x 75cm H

Technical Information

Certifications, Approvals and Ratings

UN1A1/Y1.5/300



New Pig

World's best stuff for leaks, drips and spills.

One Pork Avenue • Tipton, PA 16684-0304

1-855-493-4647 • Fax: 1-800-621-7447 • newpig.com • hothogs@newpig.com