

Quick-Style Open-Head UN Rated Steel Salvage Drum

DRM846 85 gal., UN1A2/X440/S, UN1A2T/Y320/S, 1.5/1.5/1.5 mm

Ship damaged or leaking containers of hazardous materials in these UN Rated open top steel salvage drums.

- UN Rated and tested to help ensure safe shipping of hazardous materials
- Quick-style lever lock rings make it easy to comply with closure regs; no tools required
- Open-head design and removable lid offer full, convenient access
- Shippable "as is" so there's no need to switch closure rings
- High-visibility yellow with red multi-lingual "Salvage Drum" markings clearly identify drum
- Interior is coated with a corrosion inhibitor; choose optional phenolic/epoxy lining for added resistance
- 16-gauge steel lid, body and bottom meet strict wall thickness requirements to ensure strength, durability and long life



Item#	Description	Dimensions	Weight
DRM846-LD	Lined	ext. dia. 26.56" x 39" H	80 lbs.
DRM846-ULD	Unlined	ext. dia. 26.56" x 39" H	80 lbs.

Metric Equivalent:

Item#	Description	Dimensions	Weight
DRM846-LD	Lined	ext. dia. 67.5cm x 99.1cm H	36.3 kg
DRM846-ULD	Unlined	ext. dia. 67.5cm x 99.1cm H	36.3 kg

Specifications

Lining	Lined; Unlined
Thickness	1.5/1.5/1.5 mm
Color	Red/Yellow
Dimensions	ext. dia. 26.56" x 39" H
Storage Capacity	85 gal.
Brand	Skolnik
Bung Type	No Bung Holes
Drum Type	Steel Drum
Interior Dimensions	26" Dia. x 37" H

Lid Type	Open-Head - Quick-Style Lever Lock Band
Sold as	1 each
Weight	80 lbs.
# per Pallet	4

Composition
Drum - 16-Gauge Steel
Ring - Galvanized Steel
Lining - Rust Inhibitor (Unlined), Phenolic/Epoxy (Lined)
Gasket - EPDM

UNSPSC	24112108
---------------	----------

Pigalog® Page Number [Page 313](#)

Metric Equivalent

Dimensions	ext. dia. 67.5cm x 99.1cm H
Storage Capacity	321.7 L
Weight	36.3 kg

Technical Information

Certifications, Approvals and Ratings

UN1A2/X440/S, UN1A2T/Y320/S

Technical Documents

49 CFR 173.3(c)(1)



One Pork Avenue • Tipton, PA 16684-0304

1-855-493-4647 • Fax: 1-800-621-7447 • newpig.com • hothogs@newpig.com