

20-Gallon Open-Head UN Rated Steel Drum with Bungs

DRM970 Storage Capacity 20 gal., UN1A2/X220/S, UN1A2/Y1.5/150, Thickness 1.2/1.2/1.2 mm



Tough, UN Rated open top drums are made for hazardous materials, so you can rely on them to deliver safety and compliance.

- UN Rated and tested to help ensure safe shipping of hazardous materials
- Open-head design and removable lid offer full, convenient access to inside of drum
- 12-gauge bolt ring closure, sponge rubber gasket and plated bolt/nut provide tight seal to help prevent leaks and spills
- Comes with separate lid with 2" NPT and 3/4" NPT bungs
- Interior is coated with a corrosion inhibitor; choose optional phenolic/epoxy lining for added resistance
- 18-gauge steel lid, body and bottom meet strict wall thickness requirements to ensure strength, durability and long life

Item#	Description	Dimensions	Weight
DRM970-LD	Lined	ext. dia. 19" x 21.75" H	27 lbs.
DRM970-ULD	Unlined	ext. dia. 19" x 21.75" H	27 lbs.

Metric Equivalent:

Item#	Description	Dimensions	Weight
DRM970-LD	Lined	ext. dia. 48cm x 55cm H	12.2 kg
DRM970-ULD	Unlined	ext. dia. 48cm x 55cm H	12.2 kg

Specifications

Dimensions	ext. dia. 19" x 21.75" H
Storage Capacity	20 gal.
Brand	Skolnik
Bung Type	2" NPT and .75" NPT (Tri-Sure) Bungs
Drum Type	New Steel Drum
Lid Type	Open-Head - Nut & Bolt Ring
Color	Black/White
Lining	Lined; Unlined
Thickness	1.2/1.2/1.2 mm
Sold as	1 each

Weight	27 lbs.
# per Pallet	20
Composition	Drum: Carbon Steel Bolt Ring: 12-Gauge Steel Gasket: EPDM
UNSPSC	24112108
Pigalog® Page Number	Page 290

Metric Equivalent

Storage Capacity	75.7 L
Weight	12.2 kg
Dimensions	ext. dia. 48cm x 55cm H

Technical Information

Certifications, Approvals and Ratings

UN1A2/X220/S, UN1A2/Y1.5/150



One Pork Avenue • Tipton, PA 16684-0304

1-855-493-4647 • Fax: 1-800-621-7447 • newpig.com • hothogs@newpig.com