

Zee Line Stainless Steel Rotary Hand Drum Pump - PTFE Seals

DRM988 For Corrosives; Fuels, Max Flow Rate 6 oz./Revolution, Max Viscosity 60 wt.

Quickly pump corrosive chemicals, fuels and other flammables from your drums with this versatile stainless steel rotary hand-operated pump.

- Stainless steel construction is compatible with corrosive chemicals and fuels
- Rotary design with aluminum handle provides single-motion dispensing
- PTFE vanes, stainless steel spring and PTFE seals are chemical-resistant
- PTFE tape (included) provides an excellent seal between pickup tube sections
- Moves up to 6 oz. of fluid per revolution
- Use with up to SAE 50 wt. viscosity or 880 cP
- Rubber water deflector keeps moisture from entering drum through bung adapter
- Pump can be grounded for use with fuels and chemicals
- Hose barb adapter secures a 3/4" hose (not included) onto spout for dispensing at a distance
- Safety locking pin secures handle to prevent accidental discharge
- Fits 15-, 30- or 55-gallon drums with 2" NPT bungs
- 3-piece stainless steel pickup tube and bung adapter let you adjust height



Specifications

Use With	15 to 55 gal. Drum w/ 2" NPT Bung
Brand	Zeeline
Compatible With	Corrosives; Fuels
Ideal For	Corrosives; Fuel
Manual Pump Type	Rotary Operated
Max Flow Rate	6 oz./Revolution
Color	Silver
Max Viscosity	60 wt.
Powered By	Manual

Use With Flammables

Yes

Sold as

1 each

Weight

13.61 lbs.

per Pallet

180

CompositionBody - 304 Stainless Steel
Vanes, Shaft Seal - PTFE**Includes**1 - Roll of Teflon tape for joints
1 - Pump**UNSPSC**

40151529

Pigalog® Page NumberPage 307**Metric Equivalent****Weight**

6.2 kg

Technical Information**Technical Documents**[Zee Line Pump](#)[Pump Selection Guide](#)**New Pig**

World's best stuff for leaks, drips and spills.

One Pork Avenue • Tipton, PA 16684-03041-855-493-4647 • Fax: 1-800-621-7447 • newpig.com • hothogs@newpig.com