

WeatherTech® Interlocking Stone Pattern Anti-Fatigue Mat End Section

FLM1042 Dry Applications, Polyurethane, 24" W x 36" L

Interlocking anti-fatigue mat allows you to make custom configurations to suit your workspace.

- Easily connect end, middle and corner pieces (sold individually) together with patent pending SnapLink system
- Shape it your way around machinery or workshop benches
- Can be extended long enough for several people to stand on it at once
- ¾"-thick mat helps reduce stress on feet, knees and legs from extended standing
- Surface and underside are textured to provide extra traction and grip
- Beveled edge prevents mat from being a trip hazard

WeatherTech

Item#	Description	Dimensions	Weight
FLM1042-BK		24" W x 36" L x .75" H	15 lbs.
FLM1042-GY		24" W x 36" L x .75" H	15 lbs.

Metric Equivalent:

Item#	Description	Dimensions	Weight
FLM1042-BK		61cm W x 91cm L x 1.9cm H	6.8 kg
FLM1042-GY		61cm W x 91cm L x 1.9cm H	6.8 kg

Specifications

Drainage Holes

Size	24" W x 36" L
Dimensions	24" W x 36" L x .75" H
Chemical Contact	Not for Chemical Contact
Oil/Grease Contact	Not for Oil/Grease Contact
Anti-Slip	No
Application	Dry Applications
Beveled Edge	Yes
Brand	WeatherTech

Without Holes

Grit Surface	No
Safe for Welding Areas	No
Static-Dissipative	No
Sold as	2 per box
Weight	15 lbs.
# per Pallet	30
Composition	Polyurethane
UNSPSC	52101510
Pigalog® Page Number	Page 234
1 134103 - 1 430 114111201	<u> </u>

Metric Equivalent

Weight	6.8 kg

Dimensions 61cm W x 91cm L x 1.9cm H

Technical Information

USOnly

This product can ONLY be shipped to the United States.



One Pork Avenue • Tipton, PA 16684-0304

1-855-493-4647 • Fax: 1-800-621-7447• newpig.com • hothogs@newpig.com