



## WeatherTech® Interlocking Carbon Fiber Pattern Anti-Fatigue Mat Middle Section

FLM1043 Dry Applications, Polyurethane, 24" W x 36" L

Interlocking anti-fatigue mat allows you to make custom configurations to suit your workspace.

- Easily connect end, middle and corner pieces (sold individually) together with patent pending SnapLink system
- Shape it your way around machinery or workshop benches
- Can be extended long enough for several people to stand on it at once
- ¾"-thick mat helps reduce stress on feet, knees and legs from extended standing
- Surface and underside are textured to provide extra traction and grip
- Beveled edge prevents mat from being a trip hazard

WeatherTech

Item#	Description	Dimensions	Weight
FLM1043-BK		24" W x 36" L x .75" H	8 lbs.
FLM1043-GY		24" W x 36" L x .75" H	8 lbs.

### Metric Equivalent:

Item#	Description	Dimensions	Weight
FLM1043-BK		61cm W x 91cm L x 1.9cm H	3.6 kg
FLM1043-GY		61cm W x 91cm L x 1.9cm H	3.6 kg

### Specifications

Size	24" W x 36" L
Dimensions	24" W x 36" L x .75" H
Chemical Contact	Not for Chemical Contact
Oil/Grease Contact	Not for Oil/Grease Contact
Anti-Slip	No
Application	Dry Applications
Beveled Edge	Yes
Brand	WeatherTech
Drainage Holes	Without Holes

Grit Surface	No
Safe for Welding Areas	No
Static-Dissipative	No
Sold as	1 each
Weight	8 lbs.
# per Pallet	50
Composition	Polyurethane
UNSPSC	52101510
Pigalog® Page Number	<u>Page 234</u>

## Metric Equivalent

Weight	3.6 kg
Dimensions	61cm W x 91cm L x 1.9cm H

## Technical Information

USOnly

This product can ONLY be shipped to the United States.



**One Pork Avenue • Tipton, PA 16684-0304**

1-855-493-4647 • Fax: 1-800-621-7447 • [newpig.com](http://newpig.com) • [hothogs@newpig.com](mailto:hothogs@newpig.com)